AMERICAN

Cinematographer

25c
FOREIGN 35c

THE MAGAZINE OF MOTION PICTURE PHOTOGRAPHY

SEPTEMBER
1948

DRAMATIC . . . appealing effects are readily obtained with Du Pont "Superior" 2. The extremely wide latitude of this popular, all-purpose negative stock provides ample speed to capture the subject under difficult conditions of high or low key lighting. Leading cinematographers also approve its famed uniformity of quality. E. I. du Pont de Nemours & Co. (Inc.), Photo Products Department, Wilmington 98, Delaware. New York—Los Angeles—Chicago.

DU PONT MOTION PICTURE FILM

DU PONT

BETTER THINGS FOR BETTER LIVING . . . *THROUGH CHEMISTRY*

Listen to "CAVALCADE OF AMERICA"
—Monday evenings 8 P M, E.T.—NBC

Describe your ideal camera . . . and you'll describe a

BELL & HOWELL

EYEMO



Whatever features you need in a portable 35mm camera, you'll find them *all* in one of the B&H Eyemo models

And whichever model you choose, you'll find in it a perfection of design and workmanship that results in a lastingly *dependable* camera. With an Eyemo you don't take a chance . . . you take a *picture!*



Eyemo Model Q, with 3-arm offset turret, positive viewfinder, speed range 8 to 48 frames per second, hand crank, and prismatic focuser with magnifier (for direct viewing through the lens) Provision for electric motor drive, and for external magazines as shown here.

Other Eyemos:

Model M. Has compact three-lens turret head, positive viewfinder, 8-48 speeds, and hand crank.

Model K. Has single-lens head, positive viewfinder, 8-48 speeds, and hand crank Light, compact

Eyemos are sold only direct to you from the B&H factory or branch offices Bell & Howell Company, 7148 McCormick Road, Chicago 45. Branches in New York, Hollywood, Washington, D. C , and London.

For 16mm Professional Work
it's the new
FILMO 70 SPECIALIST
Write for FREE Illustrated Literature

Precision-Made by
Bell & Howell
Since 1907 the Largest Manufacturer of Professional Motion Picture Equipment for Hollywood and the World

Auricon-Pro

16 mm Sound-On-Film Camera

Designed in Hollywood for the discriminating movie maker Camera (less lens) priced from $1095 00 complete with amplifier microphone, tubes, batteries headphones and instructions *See your dealer or write today for further information*

Features...

- Records talking pictures in black and white or color
- Completely silent in operation self blimped no noise for recording microphone to pick up
- Veeder-Root geared reset footage counter
- Auto-Parallax View-Range Finder available
- Synchronous motor driven
- Rugged Auricon "Iron-Vane" sound track recording galvanometer never needs adjustment

RCA Licensed
High Fidelity 16mm Sound-On-Film
Guaranteed One Year

Auricon Hollywood

BERNDT-BACH, Inc.

7381 Beverly Blvd., Los Angeles 36, Calif.

MANUFACTURERS OF SOUND-ON-FILM RECORDING EQUIPMENT SINCE 1932

Hollywood Bulletin Board

JAMES WONG HOWE, A.S.C., returning soon to China to resume production of his picture Rickshaw Boy, will record all the sound on magnetic tape, using one of Len Roos' recently developed magnetic tape recorders Tape used is specially treated 16mm film Howe will also carry along a compact portable 110-v generator to provide all power necessary for cameras and recorder

•

IMAGINE, IF YOU CAN, a cinematographer hoping for clouds and fog instead of sunshine on a picture assignment Well, that was A.S.C. member Elmer Dyer's prayer when he left recently for Arcata, California, to photograph in color the recently completed FIDO fog dispersal system on the government airport there Much of the filming will be done at night, and Dyer will use two B&H Specialist cameras and commercial Kodachrome film

•

JOHN W. BOYLE and Charles Rosher have been appointed a committee by the Board of Governors of the American Society of Cinematographers to work with Grant Leenhouts and Wells Root, producer and writer respectively, on the Motion Picture Industry Film Project short subject which will tell the story of the Directors of Photography and the camera craft in the industry

•

JOHN ALTON, A.S.C., is putting the final polish on the script for his forthcoming book, "Painting With Light," to be published by MacMillan Company Publishers are said to be so enthusiastic over Alton's script they have commissioned him to do another book, this time a novel

•

EVERYBODY WANTS INTO the video pictures act, according to a recent Hollywood survey which revealed that at least 51 companies have been formed there to make motion pictures for television In addition, there are companies in New York, Chicago and other cities that have plans to enter the field or are already in production on such films More recently, CBS signed with an independent producer for a series of 13 television shorts at a reported figure of $7,500 each

•

GLEN MacWILLIAMS, A.S.C., who has recently become an independent producer of 16mm business films, premiered his first production, 'Forever Angler, in Hollywood recently Film, sponsored by a leading manufacturer of sportfishing tackle, depicts the fishing sport from trout stream to deep sea and is noteworthy for its special microscopic sequence showing the treatment of fish eggs and hatching of young trout

•

DEEPEST SYMPATHY is extended by all members of the American Society of Cinematographers this month to Norbert Brodine, whose mother passed away recently, to Leo Tover, whose wife passed suddenly last month after a lingering illness, and to the widows and survivors of Robert C Bruce, one time A.S.C. member who died of pneumonia a few weeks ago after returning from a location trip in Mexico, and Sam Landers, also a former member of the Society Other notables called by death recently who were prominent in the motion picture industry were David Wark Griffith, and Edward H Amet, inventer of the Magnigraph, said to be the forerunner of the motion picture camera

•

OLLIE COMSTEDT, A.S.C., Swedish producer-director-cameraman arrived in Hollywood recently, bringing with him a set of rare zoom lenses, one of which is the only one of its kind in existence, and valued upwards of $12 000 While here, Comstedt will negotiate with cameramen and producers for use of his lenses on lease basis Lenses may be used on either 16mm or 35mm cameras One features an auxiliary lens for ultra closeups and a set of filters During the past year, Comstedt photographed a series of color films in Scandinavia, using his zoom lenses

•

RAY CORY, A.S.C., veteran process photography expert currently with Columbia Pictures, has purchased the famed 4400 acre Double-Arrow Ranch located near

(Continued on Page 324)

NOTICE
To All A.S.C. Members

The Society's second annual 'Ladies Night Dinner and Dance will be held at the A.S.C. clubhouse in Hollywood Saturday evening, September 11th, at eight o'clock It is to be a semi-formal affair and admission is restricted to members and their ladies Invitations are now in the mail and prompt attention to the "RSVP" is requested

☆

. . . tributes and billing

THERE ARE indications that some motion picture critics at least, are not unmindful of the Director of Photography's contribution in the making of a successful picture. In this space in earlier issues we have pointed out the scant attention paid the cinematographer and his work by the average film reviewer. It is therefore a pleasurable surprise to find that during recent weeks, certain film reviewers have paid tribute to the artistry of cameramen on certain productions although not all the cameramen are A.S.C. members, viz.

"Ray June's camera work is first rate throughout." (M-G-M's *A Southern Yankee*.)

"The technical contributions are expertly accomplished, particularly the photography of John MacBurnie." (Republic's *Marshall of Amarillo*.)

"And surely Gabriel Figueroa's breathtaking work cannot be overlooked this coming March at Oscar-time." (Steinbeck's *The Pearl*.)

It is also interesting to note, especially in light of what was written here last month, that in a 2-column display advertisement in a Los Angeles daily newspaper, which announced the Mexican film, *Rio Escondido*, cinematographer Figueroa's name received equal billing with that of Emilio Fernandez, the director.

This is a precedent that could well be emulated by American producers and exhibitors. It is just possible that the American public, too, is well aware of the fine work of certain of our Directors of Photography, and that it is an added incentive to see their pictures when the names of the cameramen also appear in the billing.

★

AMERICAN SOCIETY OF CINEMATOGRAPHERS

OFFICERS AND BOARD OF GOVERNORS

CHARLES G. CLARKE, President
FRED W. JACKMAN, Exec. V.-Pres. and Treas.
ARTHUR EDESON, First Vice-President
ALFRED L. GILKS, Second Vice-President
WILLIAM V. SKALL, Third Vice-President
RAY RENNAHAN, Secretary
JOHN W. BOYLE, Sergeant at Arms
John Arnold
Sol Polito
George Folsey
Charles Rosher
Lee Garmes
John Seitz
Leon Shamroy
Joseph Walker

ALTERNATE BOARD MEMBERS

Milton Krasner
Sol Halprin
Arthur Miller
Hal Mohr
Joseph Ruttenberg

Cinematographer

THE MAGAZINE OF MOTION PICTURE PHOTOGRAPHY

ARTHUR E. GAVIN, *Editor*
ESTHER TOW, *Assistant Editor* — *Technical Editor*, EMERY HUSE
GLENN R. KERSHNER, *Art Editor* — *Circulation* MARGUERITE DUERR
EDITORIAL ADVISORY BOARD: Fred W. Jackman, A.S.C., John Arnold, A.S.C., Arthur Edeson, A.S.C., Lee Garmes, A.S.C., Charles Rosher, A.S.C., Leon Shamroy, A.S.C., Fred Gage, A.S.C., Dr. J. S. Watson, A.S.C., Dr. L. A. Jones, A.S.C., Dr. C. E. K. Mees, A.S.C., Dr. V. B. Sease, A.S.C., Col. Nathan Levinson

Editorial and Business Office: 1782 N. Orange Dr., Hollywood 28, Calif.
Telephone: GRanite 2135

VOL. 29 — SEPTEMBER • 1948 — NO. 9

CONTENTS

Articles

KALEIDOSCOPIC FILTERS—*By Ray Fernstrom, A.S.C.* 301
TELEVISION CAMERA OPERATION—*By Hermas I. Smith* 302
THREE AND A HALF MINUTE TAKE—*By Bart Sheridan* 304
"T" STOPS 306

Features

HOLLYWOOD BULLETIN BOARD 296
KEEPING UP WITH PHOTOGRAPHY 298
CINE KINKS FOR MOVIE AMATEURS 311
25 YEARS AGO WITH A.S.C. MEMBERS 320
CURRENT ASSIGNMENTS OF A.S.C. MEMBERS 322
WHAT'S NEW IN EQUIPMENT, ACCESSORIES, SERVICE 324

16mm. & 8mm. Section

LIGHTING SMALL SETS—*By Charles Loring* 309
CINE MAGIC—*By Fred Jackman, A.S.C.* 310
FILMING THE STORY OF THE "GIANT EYE"—*By Sidney Zipser* 312

ON THE COVER

WILL 9-year-old Mary Clarke, daughter of A.S.C. president Charlie Clarke, one day become the first woman director of photography? With the technical assistance of her illustrious dad, Mary, who is an avid 16mm. movie maker, focuses her Filmo for a closeup of Mark Stevens. Stevens stars in "Sand," which Clarke is currently photographing for 20th Century-Fox.

AMERICAN CINEMATOGRAPHER, established 1920, is published monthly by the A.S.C. Agency, Inc., 1782 N. Orange Dr., Hollywood 28, Calif. Entered as second class matter Nov. 18, 1937, at the postoffice at Los Angeles, Calif., under act of March 3, 1879. SUBSCRIPTIONS: United States and Pan American Union, $2.50 per year; Canada, $2.75 per year; Foreign, $3.50. Single copies, 25 cents; back numbers, 30 cents; foreign single copies, 35 cents; back numbers, 40 cents. Advertising rates on application.

Copyright 1948 by A.S.C. Agency, Inc.

AUSTRALIAN REPRESENTATIVE: McGill's, 179 Elizabeth St., Melbourne.

600 PAGES OF TECHNICAL ARTICLES

written by some of the highest paid technical talent in the motion picture industry

Printed and published in 1930, a limited number of the original editions of this valuable technical book are available to cinematographers, movie amateurs, schools and public libraries.

No other book ever written contains so much data supplied by the professionals of Hollywood's motion picture studios.

Optical Science of Cinematography, Composition in Motion Pictures, by Dan Clark, A.S.C.; Painting With Light, by Victor Milner, A.S.C., Light Filters in Cinematography, by Ned Van Buren, A.S.C., Art in Makeup, by Max Factor, Motion Picture Studio Lighting, Sound Recording, Micro-Cinematographic Apparatus, Useful Facts and Formulae—these are but a few of the subjects covered in this book.

A MUST FOR YOUR LIBRARY OF TECHNICAL BOOKS

Printed on fine coated paper containing hundreds of photographic illustrations and bound in blue leatherette this book could not be produced today for anywhere near the special price asked

$3.50

Postpaid

MAIL THIS COUPON TODAY!

American Society of Cinematographers
1782 N. Orange Dr.,
Hollywood 28, Calif.

Gentlemen: Enclosed find $3.50 for which please send me a copy of the CINEMATOGRAPHIC ANNUAL.

Name

Address

City Zone State

NOTE: Foreign remittance must be made by International Money Order or in currency of the U. S.

Keeping up with

PHOTOGRAPHY

★ ★ ★

TELESHO OF CALIFORNIA
HOLLYWOOD, CALIFORNIA

UNIVERSITY OF WASHINGTON
SEATTLE, WASHINGTON

U. S. ARMY ORDNANCE DEPARTMENT

JERRY FAIRBANKS INCORPORATED
HOLLYWOOD, CALIFORNIA

DEPARTMENT OF COMMERCE
WASHINGTON, D C

DIRECTOR NATIONAL INSTITUTE OF HEALTH
BETHESDA, MARYLAND

ROBERT CARLISLE PRODUCTIONS
HOLLYWOOD, CALIFORNIA

NATIONAL FILM BOARD OF CANADA
OTTAWA, CANADA

NATIONAL ADVISORY COMMITTEE
LANGLEY FIELD, VIRGINIA

AUDIO PRODUCTIONS
NEW YORK, NEW YORK

FITZPATRICK PICTURES
CULVER CITY, CALIFORNIA

GILLETTE PRODUCTION
HOLLYWOOD, CALIFORNIA

GENERAL ELECTRIC
SCHENECTADY, NEW YORK

ARTHUR KRIENKE
PLAINFIELD, NEW JERSE

RKO PATHE
NEW YORK, NEW YORK

U. S. NAVY

CARAVEL FILMS
NEW YORK NEW YORK

ROBERT RICHIE
NEW YORK, NEW YO

RAMSEY PICTURES
DALLAS TEXAS

E. FITZGERALD
MEXICO, D F

REID H RAY FILMS
ST PAUL, MINNESOTA

WALTER S. CRAI
OMAHA, NEBRASKA

WILDING PICTURES
CHICAGO, ILLINOIS

U. S. AIR CORPS

FILMS FOR INDUSTRY
NEW YORK NEW YORK

CAMERA EQUIPMEN
NEW YORK NEW YORK

HARTLEY PRODUCTIONS
NEW YORK, NEW YORK

ARGOSY PICTURES
CULVER CITY, CALIFORNIA

NATIONAL MARITIME UNION
NEW YORK, NEW YORK

MARK ARMISTEAD
HOLLYWOOD, CALIFORNIA

ALEXANDER FILMS
COLORADO SPRINGS, COLO

U S. ARMY SIGNAL CORPS

RURAL EDUCATION OF CHINA
NANKING, CHINA

SPORTSREEL PRODUCTIONS
BERKELEY, CALIFORNIA

A. B THERMAENIUS FILMS
STOCKHOLM, SWEDEN

SOCIETE BELGE INDUSTRIELLE
BRUSSELS, BELGIUM

JAM HANDY ORGANIZATION
DETROIT, MICHIGAN

FIRST Anniversary OF THE Mitchell* 16mm PROFESSIONAL

The Mitchell Camera Corporation takes pride in announcing that during the first year on the market the new MITCHELL 16mm PROFESSIONAL has entered every field where photographic perfection is required—including entertainment, education, sports and science. We wish to extend our sincere appreciation to all our customers for their continued confidence, which has been justified by the recognition of Mitchell equipment as standard by motion picture producers throughout the world.



Mitchell Camera CORPORATION

666 WEST HARVARD STREET • GLENDALE 4, CALIFORNIA • CABLE ADDRESS: "MITCAMCO"

EASTERN REPRESENTATIVE: THEODORE ALTMAN • 521 FIFTH AVENUE • NEW YORK CITY 17 • MURRAY HILL 2-7038

*85% of the motion pictures shown in theatres throughout the world are filmed with a Mitchell



THE *Future* ARRIVES DAILY

. . . and finds Maurer 16-mm equipment ready to meet its demands





*For those who may have been educated to believe that such a result is not possible with 16-mm film, we shall be glad to demonstrate that it is not only possible, but practical commercially now

Since 16-mm sound projectors to date have been designed to reproduce only to about 6,000 cycles per second, ordinary sound-on-film recorders have been built to record only that range. But not so with the Maurer!

Anticipating a definite demand for a finer quality of recording including the higher frequencies, the Maurer Recording Optical System was designed to produce an extremely fine line image that makes possible the recording of frequencies well beyond 10,000 cycles, with very low distortion. The galvanometer of the postwar Maurer Model 10 System is tuned to 12,000 cycles. This is the model that has been sold to the trade for two years.

Now television has arrived—and it has brought a demand for high fidelity 16-mm recording. Only Maurer was ready with the equipment to meet this need, proving again the value of the Maurer policy of building, not merely for the present, but for the future.

16mm maurer

J. A. MAURER, INC.

37-07 31st Street, Long Island City 1, N. Y.

Professional Motion Picture Cameras and Recording Equipment for the Production of Industrial, Educational and Training Films





ABOVE SKETCH represents an approximate scene which auther was called upon to photograph in color. Good color was lacking in the scene, however—the sky was dull and there was considerable glare from the sea and the foreground too was virtually colorless. Employing his "kaleidoscopic filter" technique Fernstrom placed before the camera lens a composite filter which enabled him to 'paint' color into the scene by shooting through colored gelatins. How the gelatins were arranged to form the composite filter is illustrated in diagram at left.

Kaleidoscopic Filters

A new economy technique that puts color into scenes where none exists and affords the cinematographer greater control over color and exposures.

By RAY FERNSTROM, A S C

WITH ECONOMY the keynote today of every motion picture production operation including cinematography, every cameraman is digging down deep into his bag of tricks in order to cut corners and do his bit to shave production costs. One of the expense items of color productions that can be materially reduced if not eliminated entirely is that of putting color in large expansive scenes where none existed before, in order to obtain a pleasing over-all color balance in the scene. Instances are common where virtually acres of an exterior location have had to be sprayed with green paint in order that they might register properly on Technicolor or Cinecolor film. Fences have been painted and houses and barns tinted or subdued in order to satisfy the color technician's critical eye.

There is a simpler way to do this that will eliminate the need for spray painting or at least reduce its application to an area only a few square feet in extent. Also this method enables a wide new range of lighting control over exterior scenes even for black and white photography.

Before the war I wrote an article on the subject of Motion Painting that appeared in THE AMERICAN CINEMATOGRAPHER in which I described the use of graduated N D filters and pola screens in shooting color. What follows here will enlarge upon that technique and develop what I term Kaleidoscopic Filter shots.

Peering through one of my kaleidoscopic filters would suggest a view through a kaleidoscope with its multicolored pattern made up of a myriad of transparent colored pieces of celluloid of assorted shapes and sizes. Here however, the resemblance ends, for the kaleido filter's colored gelatins are arranged in a predetermined pattern and have as their purpose the function of imparting color in a scene where none exists, to correct a flat or over brilliant sky, or to subdue glare from an expanse of water—or all three.

Briefly the kaleidoscope filter consists of a panel of clear optical glass of a size to fit over the front of the camera's matte box where it is fastened securely. With this glass in place the camera is racked over to permit viewing the scene through the lens or viewfinder and, of course through the panel of clear glass. The desired composition is selected and the camera locked in position. Now using a fountain pen the areas on the glass to be covered with sections of filter gelatins are

(Continued on Page 319)



FIG 1—Front view of the TK-10A studio camera showing the four-lens turret Turret is rotated from rear Lenses are focused by means of the small hand crank shown on side of camera toward the rear which adjusts the Image Orthicon tube within the camera, moving it toward or away from the lens



FIG 2—Rear view of the TK-10A camera showing viewing head of the electronic viewfinder through which operator sees the picture output of his camera Immedrately below is the handle by which operator revolves the lens turret on front of the camera

TELEVISION CAMERA OPERATION

A brief discussion of television photography in studio and remote operations, using the new Image Orthicon cameras, and its comparison with cinematography.

By HERMAS I SMITH

Don Lee Broadcasting System Hollywood

ACTUALLY, what is involved in operating the television camera duting a telecast? What comparisons, if any, can be made to the operation of conventional motion picture camera equipment? Before discussing these questions, it might be well to describe briefly the two Image Orthicon cametas, type TK-30A and TK-10A which have recently been made available to the television industry by RCA

Both cameras are similar in size and general design The TK-10A is designed for studio operations and is shown in Fig 3 The TK-30A is generally used for remotes or on-the-spot telecasts where conditions may be adverse It was designed for this type of service, although it has been successfully used in studio work One of the principle differences between the two cameras lies in the type of Image Orthicon tube employed The type 2P23 is used in the TK-30A, and type 5655 is used in the studio camera. The differences between these tubes centers primarily in their different color response curves, and in their sensitivity to light of different levels

To make handling and maintenance easier, the cameras are built in two basic units, the camera proper and the electronic viewfindet The camera section contains the pickup tube and associated electronic circuits The viewfinder contains a five-inch picture tube and associated electronic components The cameraman, looking into the viewfinder sees on the screen of its tube the picture output of his camera As this picture is being transmitted to the camera control unit, the cameraman may obtain accurate focus and framing as well as monitor the picture quality

A photograph of the opened camera is shown in Fig 5 The left hand side of the case accommodates electronic deflection and high-voltage pulse supply components The center section contains the pick up tube its yoke focus, and alignment coils with associated mechanism The right hand side of the camera case houses video preamplifiers and associated components The entire assembled camera and viewfinder unit is shown as normally opened for inspection in Fig 6 All electrical connections to the camera are made through one cable which plugs into the base of the camera at the rear This cable terminates in the camera control unit which may be located quite a distance from the camera

The Image Orthicon pickup tubes have a semi-transparent photosensitive surface on the inside of the tube face which is located to the rear of the camera lens This area that is sensitized to light averages 1 6 inches in diameter Since the television picture aspect ratio is 4 3, this gives a maximum avetage atea to be scanned of approximately 96 by 1 28 inches

The lens turret in the front of the camera is similar to that in a motion picture camera and accommodates four lenses These may be rapidly switched into position by turning a handle on the rear of the camera A micro-switch which is built into this handle automatically cuts off the picture during the interval the turret is revolving Lens changes are made while the camera is off the air during the period when the output of the companion camera is being used Otherwise on the air the lens switch effect is not pleasing to the viewing audience

FIG 3—TK-10A studio type television camera mounted on latest type studio pedestal.



FIG 4—The TK-30A field camera on triped and dolly. Triped provides easy panning as well as elevation

The turrets of these cameras are designed to accommodate the series of Eastman Ektar lenses normally supplied for use with the Kodak Ektar camera. A wide selection of focal lengths is available which includes the Ektar 35mm, 50mm, 90mm, 135mm, also used are the RCA 8½-in, 13-in, 15-in, 17-in, and 25-in lenses. These give the cameraman a range of horizontal lens angles ranging from 50° to about 2°, depending upon the area of the mosaic being scanned. Almost any good quality photographic objective may be adapted for use with the RCA television camera provided a satisfactory mount is designed which will fit the turret.

Focusing may be accomplished in two ways. The lenses on the turret may be individually pre-set for scenes they are intended to cover. Thereafter, the focus may be corrected through use of the main focus control on the side door of the camera which moves the Image Orthicon tube assembly on a rack and pinion forward and backward with respect to the turret. The advantage to prefocussing the short focus lenses on their individual mounts is that changes may be made from one lens to the other without refocusing the main focus control. The long focus RCA lenses, for example, the 17-in and 25 in., have no provision for focusing at the lens mount. With these lenses, the cameraman uses the main control knob for focusing.

Two of the most commonly used accessories in routine television camera operations are the cameraman's cue headset and talk-back, and the viewfinder hoods. The TK-10A camera is supplied with a straight-on type hood, as shown in Fig. 2, which may be corrected for a considerable range of camera tilts. The field camera TK-30A comes with two different hoods, a straight on type and a periscope type which may be inverted depending upon camera elevation. This type comes in handy during remotes' where last minute changes may occur in camera placement. Both hoods are light in weight and easily interchanged. As for filter holders and lens shades, standard Kodak series VI attachments with appropriate adapter rings fit the Ektar lens series. The RCA telephoto lenses are supplied with metal telescoping hoods. A 16mm slide film sign projector as well as numerous other accessories are available for use with these cameras.

Field, or 'remote' telecasts are quite different from those originating in the studio. In the first place, the cameraman deals with unrehearsed action. Secondly, the control over many aspects of the production including lighting is not the same as is found in the studio. The camera positions are established on the basis of existing facilities. The cameraman may be located in a box seat at a symphony concert or atop a theatre marquee, for example. When shooting a television program subject, the program director provides the technical crew with the necessary information as to general plan for the telecast, the program sequence, and areas he wishes covered by the cameras. From there, the engineers set up the technical facilities, and the cameramen prepare the cameras for operation.

The question is often asked, How is proper exposure determined for the camera? Since the camera tube is scanning the image at the rate of 30 frames per second, the cameraman has this factor with which to work. It is difficult to establish any fixed rule at this time since the 2P23 pickup tubes are not all uniform in their sensitivity to light level and color, especially red. When working with high levels of illumination, the lenses can be stopped down to the approximate values

(Continued on Page 316)



FIG 5—The studio camera with electronic viewfinder removed and left side opened to reveal the electronic deflection and high-voltage pulse supply components. Center section contains the pickup tube, its yoke and focusing mechanism.



FIG 6—Same camera viewed from left side and with viewfinder in place but with hood raised. Viewfinder is actually a miniature television receiver showing operator the exact image and image quality being picked up by camera lens.

ROSIE'S DOLLY . . .

pictured on opposite page, is responsible for a new continuous long-scene technique which makes it possible for the actors to put some real theatre into their portrayals. Frame enlargements above illustrate new technique. Note how camera moved in and out, at same time changing angles, giving variety to the viewpoint. Scene, which screens for 3½ minutes without a single cut, features Gregory Peck and Ann Todd, stars of David O. Selznick's Paradine Case, directed by Alfred Hitchcock and photographed by Lee Garmes, A.S.C.

Three And A Half Minute Take...

How dramatic continuous scene in Hitchcock's "Paradine Case" was photographed by Lee Garmes, A.S.C., using new multi-directional camera dolly.

By BART SHERIDAN

UNSHACKLING the camera and giving it mobility, contends Alfred Hitchcock, is a requisite for effective screen drama if the dramatic film is to ascend new heights. Too often in the past — and even today — he believes, a good dramatic picture is hampered by too frequent cuts not enough continuous action. And to back up his contention, Hitchcock offers the "Paradine Case" as exhibit A in which he has applied the "continuous take" idea to the "frustrated lover" sequence. The scene runs 3½ minutes on the screen without a single cut.

A condensed version of the scene is pictured in frame enlargements from the film reproduced on the opposite page. The scene was shot in this manner because Hitchcock and Director of Cinematography Lee Garmes, A.S.C., felt that its particular dramatic quality would be jeopardized by a succession of cuts, also, Selznick's head grip, Morris Rosen, had recently devised a new kind of camera dolly which would give the motion picture camera a new freedom of mobility, and this dolly offered for the first time the means of shooting a continuous take and at the same time afforded all the variety of viewpoint that ordinarily would be achieved in a succession of takes made with the camera in different setups and at different angles.

Heretofore all camera dollies have had to run on tracks, like trains, and beyond certain limits the tracks would get into the picture. Furthermore, the ordinary dolly could only move in a straight line. Rosen's dolly rests on four fully-swivel cushion-tired wheels and is noiseless in operation. It carries the camera not only in a straight line, but around corners and at an infinite number of angles. The camera handling is such that the actors can move freely back and forth across the set, as they might on the theatre stage.

The "Paradine Case" is a behind-the-scenes love drama of the English law courts. The long take sequence is enacted by Gregory Peck and Ann Todd. Peck, who plays an English barrister, has permitted his home life to be upset by a weird infatuation for Valli, a beautiful client whom he is defending on a murder charge. In this long scene Miss Todd, who appears as the wife, confronts Peck with her knowledge of the infatuation and taunts him about his self-produced mental torture.

For the players to indulge fully the dramatic scope of such a situation four prerequisites were needed: 1) enough time for Miss Todd to work up a good "mad"; 2) freedom of movement for the players, 3) a chance for the audience to watch both principals uninterrupted by cuts, and 4) enough visual variety within the scene to avoid any hint of monotone.

To provide them Hitchcock and Garmes decided on the continuous-scene technique. Miss Todd opens the scene by speaking to Peck as she stands at a mantle at one side of the room. Still talking, she walks to the center of the room where Peck is sitting motionless. The camera pulls back and pans with her, then trucks forward to show a semi-closeup from a slightly different angle. They talk briefly, then she leans back on the table, rises, walks around Peck's desk and talks directly into the camera, which has meanwhile swiveled around behind Peck. Laughing sarcastically, she pirouettes away from Peck's desk, talks again, then marches deep towards stage rear to pick up her hat and coat, the camera again trucking and panning to keep focus and perspective in order. Finally she crosses the room again in front of Peck and closes the door to leave him in solitude.

The big advantage gained artistically is the simulation of stage continuity and the chance for the players to put some good theatre into their presentations instead of having their words and actions strung together piecemeal in the cutting room.

In the normal or non-Hitchcock directed motion picture this scene would be photographed in at least 10 and possibly 15 different set-ups. The first setup would be a closeup of Miss Todd from which she would exit to camera right. The second would be a closeup of Peck and Miss Todd entering from camera left to make a two-shot. The third would be a standard two-shot

(Continued on Page 314)



DUBBED "Rosie's Dolly" in honor of its inventor, Morris Rosen, head grip for Selznick, this unique all-angle camera dolly was nominated for an Academy award. It affords a method of getting dolly shots without crane, boom or tracks. Camera post may be elevated to a maximum of four feet. All four wheels pivot and enable camera to circle an actor in complete closeup coverage in a limited area.



ILLUSTRATED here is a striking example of the inadequacy of the present f/stop system, based on computations made in Bell & Howell laboratories. It was found, for example, that the 3-element, coated lens (A) will transmit 94% of the light, whereas the 6-element, uncoated lens (B), with more lens surfaces and elements, will transmit only 50%. Thus at the same f/stop, these lenses differ from each other in light transmittance by nearly 2 to 1.

'T' Stops

Present diaphragm markings on lenses are based on geometrical considerations and do not take into account losses of light resulting from absorption, reflection and scattering. New "T" system is based entirely on light transmittance of lens.

FOR NEARLY fifty years the world's photographers have set their lenses according to f values in the erroneous belief that, because the f/stop represents an immutable mathematical ratio applicable to any lens, the f scale provides uniformity of light transmission. For half a century photographers have been taught that any lens set at a given f/stop will transmit to the film the same amount of light as any other lens set at the same f/stop, regardless of differences in focal lengths or maximum apertures.

Actually, this has never been true. It could be true only if light passing through a piece of glass were to emerge in the same intensity with which it enters. But it does not. The transmitted light is reduced in intensity by a number of factors which vary from lens to lens, and it is the ever increasing quantity and complexity of these variables that have pushed the f scale literally out of the picture.

M. G. Townsley, in his paper presented before the S.M.P.E. convention in Chicago, in April, 1947, stated that "Motion picture photography and amateur color film are placing an increasing premium on accuracy of exposure. Reflection-reducing coatings have increased the variation from lens to lens in the exposure produced by any given f/stop because the upper limit of lens transmission has been raised to approximately 95 per cent from the old maximum of perhaps 85 per cent, so that it is now possible to have nearly a two-to-one ratio between the exposures made with two lenses having the same geometrical f/stop."

Breaking with the old tradition in one sweeping move, Bell & Howell Company becomes probably the first major manufacturer of photographic equipment to adopt the long heralded "T stop" system (the "T" denotes "transmission"), having announced that its forthcoming entry into the still camera field — the new Bell & Howell "Foton" camera — will carry a lens calibrated in T stops rather than in the universally used f/stops.

Hollywood's cinematographers, too, have finally had enough of the inaccuracies of the f/stop, according to Bell & Howell Company, and are converting to the T stop standard. The company has just finished calibrating 60 lenses in T stops — ten matched sets of six lenses each — for Warner Brothers studios.

The amateur photographer may wonder how, if all this is true, we have been able to use exposure meters for all types and makes of lenses without any adjustment or compensation. In the answer lies recognition of the deficiency of the f/stop system. If the f/stop system meant absolute uniformity (100% light transmission), exposure meter scales would be calibrated on the basis of 100% transmission. But they are not. One of the most popular meters on the market calibrates its f/stop scale for a lens having 76% light transmission. It is recognized that this will be less than some lenses and more than others, but that an average is the best solution possible. The latitude of the film must take care of the actual variation.

Bell & Howell clarifies its statement condemning the f/stop system to oblivion by enumerating the factors responsible for the inaccuracies:

1. *Lens Surfaces.* Every lens surface causes light loss by reflection. The more elements in a lens, the more surfaces to lose light.
2. *Lens Elements.* When light passes through glass a certain amount of light is lost by absorption. Thus, the more elements in a lens, the more light is absorbed.
3. *Optical Glass.* Certain types of optical glass absorb more light than other types.
4. *Coating.* Lens surfaces that are coated lose only 1% of light by reflection. Uncoated surfaces lose 4%.

(Continued on Page 318)

TO BE SURE!

Always use

EASTMAN

Professional

Motion Picture Films

Both 35 and 16 Millimeter

Black & White

and Color Films

J. E. BRULATOUR, INC.

Exclusive Distributors

Sometimes they look as if they were pasted on!

DISAPPOINTING, isn't it, the way the people in home movies often look flat and unreal—as if they had been cut out and pasted on the background.

And yet, for years now we've been telling you that Ansco Hypan film can bring you sharp, clear screen images, that look fresh, and lifelike.

See how the boy stands out above—natural looking, full of snap. That's the kind of lifelike look we mean.

We've often referred to it as the "theater" look that professionals get in their movies. It helps put your home movies in the professional class.

Hypan film helps you get this "theater" look, with its fine grain—its pleasing scale of tone values—and its splendid panchromatic color balance.

Any dealer can tell you more about Ansco Hypan film. In both 8mm and 16mm sizes. **Ansco, Binghomton, New York.** A Division of General Aniline & Film Corporation.

TIPS ON TITLES—If you're taking shots in the country this fall, you might try cutting out large cardboard letters for your lead title, and pegging them on the side of a hay stack. Paint the letters white, to show up against the hay.

ASK FOR

Ansco

8 and 16mm

HYPAN FILM

LIGHTING SMALL SETS

First of a series of articles dealing with lighting as applied in modern 16mm. industrial film production.

By CHARLES LORING

THE PAST few years have seen greatly increased public interest in 16mm industrial, documentary, advertising and sales training films The currently booming medium of television has also created a tremendous demand for 16mm short subjects and 'commercials' As a result, many cameramen both advanced amateur and professional, are switching their talents to 16mm film production In advancing from home movies to more complex forms of movie-making, the amateur cameraman is often uncertain as to the types of lighting to use, the equipment needed, and the extent to which he can adapt for his use the lighting techniques which are standard in professional film studios With the aim of answering some of these questions, we shall attempt to analyze the overall lighting problem and perhaps provide some useful information for those just entering the fields of professional or semi-professional production

THE AVERAGE 16mm studio set being smaller, does not require the array of large lighting units commonly found on Hollywood sound stages The Bardwell & McAlister Dinky-Inkie Baby Keg-Lite and the Mole-Richardson Double Broads Pan Light and Baby and Junior spots are the lighting units most commonly in use in these studios

THIS SET, erected on the Raphael G. Wolff Studios' stage in Hollywood for Kelvinator's 16mm film production "Of This We Are Proud," is typical of the average 16mm studio set and shows some of the smaller and widely versatile lighting units used for illumination

The professional cinematographer, of course, is not unfamiliar with modern studio lighting equipment It is possible, however, that some may not be entirely familiar with many of the smaller lighting units which have found favor with producers of films on the more limited 16mm studio stages These cameramen not only will find much in the way of useful data in the descriptions that follow here, but should gain much helpful information on lighting practices as applied to small sets, in subsequent articles

The first important consideration is, of course, *equipment* Just what kind of lighting units are to be purchased and *how many* of each will depend upon the actual needs of the cameraman, as well as upon the budget available for such equipment These two elements may conflict, but nevertheless the cameraman should have available at least a minimum of units necessary to achieve the photographic quality the professional field demands

The cameraman must first analyze his own needs Will he be shooting mostly black and white, or color? Will he have to light large sets, or will he confine his activities to filming small areas? Will most of his interiors be shot in a studio or on location? The answers to these questions will determine the kind of units he will need and how many of each If he intends to shoot interiors in color, for example, he will need three or four times the amount of light he would require for black and white filming If he plans to light large sets, either in the studio or on location, he will need large units capable of flooding a good-size area with general illumination If he intends to shoot

(Continued on Page 322)



FRED W JACKMAN A.S.C former head of Warner Bros., special effects department shows an 8mm cameraist how to mount his camera for reverse action shots A simple bracket made from a length of strap iron is secured to tripod pan head and the camera mounted upside down at the opposite end At right is closeup of mounted camera which may be tilted or panned in the usual manner

Cine Magic

Turn your camera upside down for some startling trick effects in your home movies.

By FRED W JACKMAN, A S C

THE FOUR basic effects from which the majority of motion picture trick shots stem are reverse motion, double exposure, stop motion, and matte shots These devices were the basis of many of the old Keystone comedy gags and of much of the spectacular trick shots which featured early day serial films They are just as valid today for the amateur's use and are as easy to accomplish

One sure way to break the monotony of straight photography in home movies is to work in a trick or gag shot occasionally—not too often, but just enough to cause your audience to perk up and give more than passing notice to your cinematographic skill

No matter whether you are shooting movies around the garden, say of the family, the dog and the kiddies, or on an outing or a vacation trip, many opportunities will present themselves for giving your picture a new and interesting twist with a trick shot—providing you are familiar with trick filming routines And the best way in which to familiarize yourself is to study trick camera effects then deliberately set about to shoot a few and screen them, in order that you may see for yourself how simple they are to make and how effective they are on the screen

One of the simplest trick filming procedures is to shoot a scene or sequence with the camera held upside down What results is reverse motion —the action you photograph appears on the screen in reverse If you shoot a person walking toward you, for instance—with the camera upside down—on the screen this shot will show your subject walking backwards Any other action in the scene—moving automobiles, a boy pedaling a bicycle, a dog trotting along the sidewalk—all will appear moving in reverse Of course, to get the film to screen this way, it becomes necessary to cut the trick scene out of the roll of film and turn it end for end, then splice it back again, so that the scene will not appear upside down on the screen But then, you probably have figured this out yourself

The example cited above is by illustration, of course You wouldn't make a trick shot of a person walking backwards just for the trick in itself, too trite But suppose you are shooting movies in your own backyard next Sunday with your wife and kiddies and the family dog as subjects You probably have roll after roll of the baby crawling, toddling, walking, and of mother fondling, feeding, and strolling with her, now it's time you shot your family record films with a little continuity so they will have more appeal for others on the screen After all, what's the use of making home movies if they aren't interesting enough to screen for your family, friends and neighbors?

So, for an interesting sequence you arrange for mother and baby daughter to give the dog a bath The tub prepared on the lawn, mother and daughter look around for the dog You make a close shot of him watching from a distance—over by the hedge or corner of the house As daughter calls to the dog and starts to walk toward him, he backs away and disappears into the hedge or around the house He knows what's up, and he doesn't want to take a bath

Mother and daughter give chase and occasionally you pick up the dog emerging from under the house, from around the corner or from under a shrub And as soon as mother and baby appear, he backs

(Continued on Page 314)

Cine-Kodak Eight-25 Camera The "Economy Eight" makes 20 to 30 scenes on a single, inexpensive roll of 8mm. film. Built-in exposure guide; full-vision finder; footage indicator; accepts lens attachments in easy-to-use Z mounts; fixed-focus f/2.7 *Lumenized* lens, fast enough for wonderful movies, indoors and out. Its "budget price"—only $55, plus tax.

Cine-Kodak Magazine 8 Camera The camera that makes movies as easy as snapshots. To load, you simply slip in a magazine of film and close the cover—you're set to shoot! Four speeds, including real slow motion; exposure guide; standard and accessory lenses, all served by an adjustable finder; fast f/1.9 *Lumenized* lens. $125, plus tax.

A CINE-KODAK CAMERA...

your best bet for personal movies

Cine-Kodak Magazine 16 Camera The 16mm. counterpart of the Magazine 8 . . . provides comparable movie-making features, including 3-second loading. Choice of speeds; exposure guide; adjustable finder; footage indicator; scene-length guide; accepts a full complement of accessories; f/1.9 *Lumenized* lens. $150, plus tax.



Cine-Kodak Special II Camera The new Special II meets the requirements of all fields served by 16mm. movies. No wonder it's the goal of every movie expert! Integral controls make possible scores of special effects—fades, dissolves, animations, masked shots, varied-speed movies, multiple exposures. With Kodak Cine Ektar f/1.4 Lens, $860, plus tax on lens only.

EASTMAN KODAK COMPANY, Rochester 4, N. Y.

"KODAK" IS A TRADE-MARK

(Prices subject to change without notice)

Kodak

SIDNEY ZIPSER, Technicolor Corporation technician, and the Cine Special he used in photographing 'The Story of Palomar.' On front of camera is special wide angle lens attachment Zipser built which enabled him to photograph interiors within the limited area of observatory dome at Mount Palomar.

FILMING THE STORY OF THE "GIANT EYE"

Some of the technical problems encountered in photographing, in 16mm. color, the origin, construction and installation of Palomar 200-inch lens.

By SIDNEY ZIPSER

"THE STORY OF PALOMAR" was photographed in 16mm Commercial Kodachrome with a Cine Special over a period of eighteen months and is now a finished four reel picture with sound, which will be released and distributed by the California Institute of Technology

The now justly famous 200-inch Hale Telescope at Palomar Mountain in Southern California is one of the great scientific and engineering achievements of all time It is of particular interest to photographers because is is actually the largest camera ever built—a powerful instrument having a focal length of 55 feet and with a main objective having a diameter of 200 inches

Making a documentary picture of the origin construction and installation of this gigantic lens was a challenging opportunity and an education in itself, for astronomy has always kindled the imagination of men The actual building of this giant telescope over a period of twenty years at a cost of six million dollars was to me a far more dramatic and significant photographic subject than combat photography, or the photography of newsreels, travelogues and musicals with which I have worked during the past fifteen years

Mr Edison Hoge, who is on the scientific staff of the Mt Wilson Observatory, and myself had discussed the possibilities of making this picture at a Caltech alumni meeting a year and a half ago At that time the remarkable 200 inch Pyrex disk was still being polished in a specially built optical shop on the Tech campus, a "figuring" process which had already taken over ten years' This dramatic sequence would be necessary for any documentary picture, and so we started off by seeing what could be done about filming it Only the technicians actually working on the disk were allowed inside the shop, as a minute particle of grit, if tracked in and carried to the rouged water or mirror surface, would damage that surface enough to set the entire project back for several years The technicians on the project always carefully washed themselves and changed to white clothes and shoes before entering the shop, just as surgeons do in preparing for an operation Also the machines and floors were constantly scrubbed and a specially designed "electric broom" was used to remove any metal particles that might have been tracked in or 'nicked" off some of the numerous machines and other equipment inside

Finally, we were able to complete this sequence, largely due to the careful cooperation of Marcus Brown, who was in charge of the shop, and his associates, We used brand new incandescent lamps, stands, and special cables rigged for this job This equipment was rigidly inspected, cleansed and placed by the opticians themselves, the number and placing of the lamps being further restricted by the temperature rise on critical parts and by "kicks' in the faces of some of the men which might endanger their work Extreme undercranking was necessary for the establishing shots photographed from the glassed-in visitor's gallery over 100 feet away and the machinery and men were slowed down as much as possible without interfering with the process For closer shots, Hoge and I were finally admitted inside the inner sanctum after repeated warnings, careful scrubbing and the removal of our shoes, just as would be done in a Moslem mosque The dramatic close-ups obtained show how the finest and most painstaking optical job in history was accomplished

Seeing the mirror being polished brought up many related questions Why build such a big telescope? Why is a reflector used instead of a convex lens, as in the simple tubular instrument we used to see on street corners when we paid a dime to observe the Moon or Saturn? How are telescopes designed, built and operated? What is seen and photographed through them? How does this observation and research affect the average man?

If a documentary picture could answer these questions in addition to being a photographic record of an amazing scientific and engineering achievement, it ought to be of considerable interest to laymen and students and a fair distribution might be expected Thus, I reasoned, the considerable time and expense involved in the making of it would be justified

So one week-end, through Mr Hoge's arrangements, we started working at the Mt Wilson Observatory with a tough script There was a conventional six-inch telescope similar in principle to Galileo's, which afforded an introductory sequence-Then the 100-inch reflector there, the largest existing telescope at that time, was used to demonstrate (with the aid of

(Continued on Page 320)

Nothing else like it—

THE ORIGINAL AND ONLY TRUE INCIDENT LIGHT EXPOSURE METER

The NORWOOD Director

SOMETHING NEW UNDER THE SUN!

After a generation of determining exposure by reflected light readings, the NORWOOD DIRECTOR, *incident light* exposure meter was developed. Tens of thousands of photographers, professional and amateur, at once recognized the merit of a photoelectric meter designed especially to measure all of the light falling upon the camera side of the subject, i.e., the *incident* light. Here was something new—scientifically correct, and practically infallible in determining the one best shutter and diaphragm combination for every shot. Therein lies the secret of the tremendous success and great demand for the NORWOOD DIRECTOR!

THE METER WITH THE PATENTED PHOTOSPHERE*

Only the Norwood Director is equipped with the amazing Photusphere—the 3-dimensional light collector and integrator which gathers and distributes directly to the photoelectric cell all of the incident light illuminating the camera side of the subject.

SWIVEL-HEAD

The Photosphere, mounted in a swivel-head, permits turning in any direction for light gathering and leaves the dial always facing the photographer for quick readings. This is also an exclusive feature of the Norwood Director

*REG. U. S PAT. OFF

ACCURACY—Tests have proven the superiority of the incident light method of determining exposure; thousands of owners have written unsolicited testimonials as to the accuracy of the Norwood Director. Make the Norwood Director, the finest of all exposure meters, a companion to your camera and you will produce prints of which you will be mighty proud.

CONSISTENCY—Whether your shots are made indoors or outdoors, closeups or landscapes—regardless of a great variation in shutter speeds and diaphragm stops used—your black and white negatives and kodachrome transparencies, made at the direction of the NORWOOD, will have a consistent density.

The NORWOOD DIRECTOR was designed primarily to measure incident light; it is the only true incident light exposure meter.

CALIBRATION CERTIFICATE

The Norwood Director is a precise instrument manufactured to close tolerances and referenced to the internationally known standard—the foot candle. Calibration is made in reference to lights supplied by Bureau of Standards and other nationally known laboratories. Every Norwood Director is given a final, four point calibration check and the performance of the meter is recorded on a certificate and packed with that meter thereby assuring the purchaser of the accuracy of his instrument when it left the factory.

COMPLETE with steel case, neck cord, Instruction Manual, ASA Indexes, Registration Guarantee Card and Calibration Certificate

$29.95 PLUS TAX

Write FOR ILLUSTRATED BOOKLET, "CORRECT EXPOSURE DETERMINATION." DEPT. N-D.

AMERICAN BOLEX COMPANY, INC., 521 FIFTH AVENUE, NEW YORK, 17, N. Y.

Cine Kinks

For Movie Amateurs

A FADING GLASS may be made by smoking a rectangular panel of thin glass. Hold the glass over a smoking candle flame and coat the glass with smoke soot, graduating the application from clear to full opaque.

•

PROTECT your projector and editing equipment with jackets made of pliofilm. Material is available in yardage and may easily be stitched on a sewing machine. Pliofilm covers for food mixers make excellent covers for home movie projectors, photo enlargers.

•

INSURE SAFE RETURN of your movie film from the processing laboratory, by printing your name and address on the carton as soon as you purchase film. Film mailed in haste, is often mailed with owner's name and address omitted.

•

TINTING titles photographed on black and white positive film makes them more appropriate for use with color film. Use regular photo tints, available in camera stores, or use Skript writing ink, Diamond Dyes or Rit. Soak individual title film strips in water, to soften the emulsion, then immerse in tray containing the dye solution. Sponge well and wash in clear water, then hang up to dry.

•

EFFECTIVE TRANSITIONS between two scenes can be made by having one of your subjects walk right up to the camera to black out the scene, then begin the next scene by having the same player walk away from the camera until the new scene is fully revealed.

•

WHERE PROJECTOR NOISE interferes with sound played by records with your movies, soundproof it with a blimp made of an ordinary corrugated carton. Cut hole in carton to allow passage of light from lens, also an opening at top to allow exhaust of heat from lamphouse. Place blimp over projector after starting the motor.

•

AN EXCELLENT EMERGENCY projection screen can be made by mounting an ordinary bed sheet over a curtain stretcher. Iron the wrinkles and creases out first.

•

FADES IN TITLES CAN be made by simply dimming the illumination. Connect a rheostat or a Dim-A-Lite switch to the current supply leading to your lamps to raise and lower the lamp voltage.

THREE AND A HALF MINUTE TAKE

(Continued from Page 307)

from a straight-on angle. The fourth would be another closeup of Miss Todd as she exits to camera left. The fifth would be a closeup shot of her, the camera panning as she circled the table.

The sixth would be a shot of her over Peck's shoulder, seventh and eighth would be closeups of Peck, shot over Miss Todd's shoulder to complement setups five and six. The ninth would be another pan shot of Miss Todd as she executed her pirouette and exited to camera left. The tenth would be a close-up of Peck reacting to the pirouette, from Miss Todd's angle. The eleventh would be a pan shot of Miss Todd walking towards the sofa. The twelfth would be a close-up of her teaching for her hat and coat and exiting camera right. The fourteenth and fifteenth would be closeups or pans of Miss Todd as she exists from the room.

With 15 strips of film to work into the scene, the cutter would have inserted 20 to 30 cuts (because each cut may of course be used two or three times in the same scene) by the time the finished prints reached the screen. This would mean that the audience would watch the screen flick to a different subject or angle some 20 to 30 times instead of none at all as in this Hitchcock scene. Of course Hitchcock did shoot a closeup each of Peck and Miss Todd as protection in case of a hidden flaw in some frame of the big scene, but at the most this would mean a single cut over the bad section of original film.

Mottis 'Rosie' Rosen's dolly, of course must be given due credit for making the scene possible and Rosen credited with devising one of the most important cinematographic aids in recent years. Made without blueprints at a cost of $1 700 and nominated for an Academy award the dolly comprises three basic elements: small square platform, camera post and wheels. It will travel through any normal double door. The camera post, which is elevated and retracted mechanically may be raised to a maximum height of four feet from floor of dolly. All four wheels mounted on swivel bases, can make a full 360 degree turn. They are connected with one another and with the steering column by a roller chain so that all four turn simultaneously and in the same direction.

Its evolution and the effective demonstration of it by Hitchcock and Garmes sets another precedent in motion picture photography which is bound to exert a salutary influence in the planning and photography of dramatic motion pictures of the future. ★ ★ ★

CINE MAGIC

(Continued from Page 310)

out of sight. But he backs up once too often—this time right into daughter's hands, who hurries him off to the tub.

Shots of the dog backing away would be almost impossible to film unless the dog were a trained one. So you turn your camera upside down and shoot as the dog moves forward—from around the corner of the house, from under the shrub, from the hedge, etc., as someone calls to him. And when this scene is cut from the roll of film, shortened to the right length, then re-spliced—you will have just the action called for.

While you've got the family assembled, here's another trick shot you can make. Mother cautions baby she must not eat the banana in the fruit dish on the table. But baby, left alone, disobeys and is caught in the act with the banana half eaten. Make a shot of mother as she discovers the child, then cut to a brief closeup as she expresses chagrin over child's disobedience, then cut to child—this time with camera held upside down. Now shoot while the child peels and eats half of a fresh banana. When you cut this shot out and reverse it then splice it back again, the child will appear on the screen—not eating the banana—but disgorging it and the banana becoming whole again, even to the skin folding back in place! And baby caught in the act, undoes her misdeed and replaces the banana in the dish.

Many ambitious amateurs undertake the making of safety education films often to aid civic safety drives, sometimes for a local school, and not infrequently as a business venture. Invariably the script calls for a shot showing a lad on a bicycle being run down by an automobile. Making this shot appear realistic has not always been easy for some. To film an actual accident would be almost impossible and, of course, too dangerous to risk. The right effect, however, can easily be accomplished by shooting the action in reverse.

With the camera mounted upside down on the tripod, aided by a suitable bracket the action takes place in *reverse*. It must be carefully staged. The lad is sprawled over his bicycle in front of the stopped car but in such a position that he can easily rise and bring his bike erect on

cue The cue called, he goes through this motion and backs away toward the curb At the same time, the automobile backs away.

When this scene is cut out and reversed in the film, the auto will appear to meet and strike down the boy as he rides carelessly in front of the oncoming car. Skillful cutting aided by one or two cover up closeups of the terrified motorist ostensibly braking to a stop, or of his locked wheels skidding, complete the illusion.

The knife throwing gag was always good for a thrill sequence in early day silent films and indeed is occasionally used today in comedies It's so easy to do that you'll want to try it next time you have a dart game going in the patio or playroom Instead of using knives, use darts as the medium of your subject's skill or villainy.

The trick is accomplished by *pulling* the darts out of the target, one by one, as your supposedly terrified subject watches them whizz by his head, while your camera, mounted upside down, records the action Tie stout threads to the darts, long enough to reach beyond camera position Then have your subject take place in front of dart board Stick darts into board on either side of his head If background is predominantly

HARD-TO-GET ITEMS

- **MITCHELL STANDARD** 35mm F2, 50mm F2, Cooke Speed Pancros, 75mm F2 3, 100mm F2 3 Astros Coated 110 v AC-DC Variable Speed motor, 2—1000 foot magazines, Mitchell finder, Matte box, Mitchell Freehead tripod, Baby and Hi-Hat, Automatic Buckle switch, cranks, Case, PERFECT **$6000.00**
- **B&H SHIFTOVER** 35mm F2 3, 50mm F2 3 Astros, 75mm F3 5 Goerz, 6" F4 5 Zeiss, Mitchell Finder, Mattebox, 110 v AC-DC Cinemotor, Mitchell freehead tripod, baby, Buckle switch, cranks, cases, new condition, PERFECT **$4750.00**
- **ARRIFLEX,** latest model, vertical baffles, 3 Zeiss Coated lenses, 2—200 foot magazines, case **$1250.00**
- **EYEMO** 71Q, 1" F2 3, 2" F2 3, 4" F2 9 Lenses, 12 or 110 v motor, 400 ft magazines, case **$1400.00**
- **MOLE RICHARDSON DOLLY**, geared Pan and Tilt head, heavy duty balloon tires **$1100.00**
- **MOVIOLA**, 35mm, one picture and one sound head, amplifier **$850.00**

WRITE FOR "MART MESSAGE"

THE CAMERA • MART, INC.
70 WEST 45TH STREET
NEW YORK 19, N. Y.
WORLD-WIDE SERVICE
CABLE ADDRESS: CAMERAMART

The Fonda Top-Friction Drive...



eliminates film slack

Film slack is the number one problem in film developing. Fonda's patented drive mechanism completely eliminates this problem... making the Fonda developer the most efficient and most economical yet designed Stainless steel construction... almost any speed range... processes any type film 35mm, 16mm, black and white, positive, negative, reversal or microfilm.



Patented Top-Friction Drive Mechanism

Send for FREE descriptive booklet:

Compare the Fonda machine with any other make by sending for your complimentary copy of the new illustrated booklet giving complete details of the Fonda Film Processor

Address Fonda Division, Solar Aircraft Co., 2286 Pacific Highway San Diego 12, Calif.

FONDA FILM PROCESSING EQUIPMENT DIVISION

SOLAR STAINLESS PRODUCTS

San Diego 12, Calif. . . . 60 E. 42nd St., New York 17, N. Y.

Closing Out Studio Spots

LACO 2000 WATTS Large fresnel lens Mogul socket U type yoke mounts to any pedestal with 1 dia stem Cable plug and shield Value $150 like new **$57 50**

JUNIOR 2000 WATTS MR type large mirror fresnel lens bi post socket Adjustable stand on casters 4'9" to 8'6" brand new including tax **$99 50**

BARDWELL McALISTER Portable Telescopic Tripod Stands with rubber wheels extends 12 Three brackets for spots Government Surplus **$24 95**

SOS EXTRA SPECIALS OF THE MONTH

35mm Sound Film Recorders with sync motor **$1545 00**
W E & Simplex Prev ew Magazines worth $750 **395 00**
Auricon Double System 16mm Recorder comp w ampl used **495 00**
Berndt Maurer 16mm Sound Recording outfit worth $3500 **2275 00**
Arriflex 35mm Camera 4 lenses comp **895 00**
Neumade 35mm Film Racks 76" high new **39 50**
Mitchell Plywood Blimp excellent **149 50**
Houston 16mm KIA Film Processors rebuilt **3495 00**

Everything for Studio Cutting Room & Laboratory Lights Mikes Booms Dollies Lenses Background Process Moviolas etc Send for catalog Sturelab 7 —thousands of good buys!

S. O. S. Cinema Supply Corp.
Dept. AC, 602 West 52nd St , New York 19

DIRECT 16MM SOUND
with MAURER RECORDING SYSTEM

For the Producer of 16mm Business Educational and Religious Films

- Edge Numbered Work Prints
- Synchronized Studio Photography
- Sound Recording
- Release Prints— Color and B&W
- Duplicate Negatives

GEO. W. COLBURN LABORATORY, Inc.
164 N. Wacker Dr., Dept. A . Chicago 6, Ill.



AUTOMATIC DISSOLVE ATTACHMENT for CINE KODAK SPECIAL
Model A **$49.50**

JOSEPH YOLO
5968 Santa Monica Boulevard
Hollywood California

dark, tie black threads to darts, and if light, use white thread so that threads will not register in the picture and thereby spoil the illusion

On cue, as your camera starts to turn, your subject registers fright and watches the darts at either side An assistant, working outside camera range, pulls the darts out one by one by jerking sharply on the threads Shoot some of the dart action in tight closeups to lend variety to the sequence When the scene is cut out and reversed in the film the darts will appear to enter the scene with a flash and imbed themselves in the board close to your subject's head More realism will be lent the scene if you cut frequently to closeups of the dart thrower just as he releases a dart

Other illusions possible with the upside down camera are a diver springing up from a pool to the diving board, a man jumping to top of a high wall or shed, a kitten backing away from a strange new pet, a man effortlessly gathering a load of kindling — the pieces jumping magically into his arms, making a board grow in length by sawing off small sections, etc

And if you take your vacation by rail this year, you can make an effective scenic shot of the countryside as viewed from front of the locomotive, but without mounting your camera on the cowcatcher to do it Simply shoot from the rear platform of the train as it moves holding your camera upsidedown When the scene is cut out, turned end for end and re-spliced into your film, it will have all the illusion of having been shot from front of the locomotive

In keeping with the frequent admonition to 'always use your tripod' when shooting movies, you can mount your camera on your tripod in inverted position by providing a simple accessory consisting of a 12" length of ¼ inch strap iron Drill quarter-inch holes about a half inch in from either end to take the conventional tripod screw Mount this bar on tripod, using a ¼-inch No 20 thumb nut Mount your camera upside down at the other end, using a regular tripod socket screw which you can buy at any camera store

Making reverse action shots is slightly more difficult for the 8mm filmer than for the 16 because 8mm film, having only a single row of sprocket holes, not only must be turned end for end, but also turned over to bring the sprocket holes in line with rest of the film Thus the emulsion side of the film strip joins with the glossy or base side of the two film sections to which it is to be spliced. Sometimes this results in slight out of focus on the screen, but this can be corrected by quick adjustment of the lens as projection progresses

Any deviation, any improvement in your filming, naturally takes a little more pains. But it's worth it as you will invariably discover from the reaction of your friends when they see your pictures on the screen Keep in mind one thing however don't inject a trick shot into your picture just to display your ingenuity Use it logically — make it a part of the continuity — and the whole effect will appear more professional

In a future issue we shall describe the application of other professional trick effects to 8mm and 16mm movies

TELEVISION CAMERA OPERATION

(Continued from Page 303)

that would be used with movie cameras using very fast panchromatic film at 24 frames per second In the final determination of satisfactory lens settings for a given scene, the cameraman and video engineer can carefully check the electrical response of the camera itself

The video engineer has before him at the camera control a continuous oscilloscope picture that shows the electrical output of the camera The optimum lens settings can be worked out on the basis of this information Lens settings should be uniform regardless of the small differences noted on the F-setting scales of each lens so that no appreciable variation in the output of the camera is evidenced as the lenses are switched

At the last Santa Claus Lane parade in Hollywood, it was possible to make comparisons between the TK 30A field camera and standard newsreel motion picture cameras In operation, the cameras were located side-by-side on the newsreel platform Essentially uniform lighting was provided for the general area which allowed the newsreel men to work at an exposure of F1 5 at 24 frames for fast panchromatic film The TK-30A had no lenses on the turret that were faster than F3 5, but good picture quality was obtained with the 17-in F5 telephoto which was used for extreme close-ups of celebrities who were riding on the floats The newsreel cameramen who inspected the TK-30A were quick to note the brightness and clarity of the picture in the electronic viewfinder At very low light levels, as the motion picture cameraman knows, an optical viewfinder is not always satisfactory Here the tele cameraman has an advantage in that he can easily adjust the contrast and brightness of his viewfinder picture to suit his requirements

A discussion of lighting for television could become lengthy In general, lights, and lighting setups suitable for motion picture work are also satisfactory for television when the Image Orthicon camera is used However, it is important that the spectral characteristics of the light source closely approximate the response curve of the pickup tube if maximum efficiency is to be realized The type 2P23 tube has great sensitivity to light in the red end of the spectrum The type 5655 studio tube has good sensitivity to the blue Both tubes have good response to the visible spectrum, the exact response curve being a characteristic of the individual tube

Of the two types, the 2P23 tube, according to the manufacturer, is approximately 10 times more sensitive For studio work, light levels from 50 to 300 foot candles should be sufficient for high quality work The 2P23 has yielded a good studio picture with key lighting of about 5 - 10 foot candles The definition of the picture decreases considerably at very low light levels There are other factors that also enter into the problem which concern the electronic aspect of the picture

Much improvement has been made in picture pickup tubes since the time when two- to five-thousand foot candles of illumination were required for television studio shows Those who work on the television stages today appreciate the great reduction of heat that has been made possible with the use of less lighting facilities

There is quite a contrast between the operation of a motion picture camera and a television camera Except in very rare cases, the average take with a motion picture camera ranges from a few seconds to one or two minutes With the television camera—shooting studio shows or remotes—the cameraman is alert and operating the camera every second during the program interval, which may be as long as two or three hours

Watching the viewfinder picture intently, he must follow the action and anticipate cues to cover his fellow cameraman when a picture cut is ordered by the program director in the control room His double headphones carry the director's instructions to one ear and the program sound to the other. Whenever the red signal light flashes 'off' in his viewfinder, he knows his camera is momentarily off the air and this usually accompanies instructions to switch lenses or get ready to take a new scene

Rotating the handle at the rear of the camera, he quickly brings the right lens before the camera tube then corrects it for focus and framing He must also check in an instant the content and composition of the picture for, in a second or two he may be back on the air A success-

"PROFESSIONAL JUNIOR" CAMERA EQUIPMENT

Interchangeable - Removable Head Tripods

FRICTION TYPE

Handles 16mm EK Cine Special with or without motor 35mm DeVry, B&H Eyemo with motor and 400' magazine, and all 16mm hand-held cameras Head is interchangeable with the Gear Drive head Both types fit 'Professional Junior' standard tripod base 'Hi-Hat' and 'Baby' all metal tripod base



STANDARD TRIPOD BASE

GEAR DRIVE

The head, made of Dow Metal, weighs but 5½ lbs and is interchangeable with the friction type head It handles all types of cameras Snap on metal cranks control pan and tilt action from both sides Worm-driven gears are Gov I spec bronze

BLIMP for 16mm. E. K. CINE SPECIAL

This Blimp, constructed of Dow Metal is thoroughly insulated to afford absolutely silent operation Has many exclusive features that allow focusing and lens calibration changes from the outside while taking pictures Blimp takes synchronous motor drive which couples to camera A dovetail bracket is provided to mount an erect image viewfinder

SUNSHADE & FILTER HOLDER COMBINATION



For use with all popular types of 16 mm cameras Holds two 2" sq. glass filters and a round 2½" Pola Screen with handle which can be rotated for correct polarization Covers all lenses from 15mm to 6" telephoto and eliminates need of many other filters Precision made of the finest materials Compact, simple to assemble and dismount May be permanently affixed to camera or can be taken apart to put into camera carrying case

—ALSO AVAILABLE—

BABY TRIPODS **3 WHEEL PORTABLE DOLLYS**
CHANGING BAGS **"HI-HATS"**

Send for our catalog. It describes all our products completely

FRANK C. ZUCKER
CAMERA EQUIPMENT CO.
1600 BROADWAY NEW YORK CITY

"Goerz American"

PRECISION PHOTO-LENSES

An American Product Since 1899

will give you a lifetime of profitable satisfaction

GOERZ DAGOR F6.8
The favorite universal all-purpose lens, color-corrected wide-angle convertible—for interiors exteriors commercial and amateur work, scenic views groups banquets color film copying enlarging

GOERZ SUPER DAGOR F8
The wide-angle lens greatly extended coverage convertible

GOERZ DOGMAR F4.5
The perfect speed lens color corrected convertible For news sports portraits general work color film

GOERZ ARTAR F9 TO F16
The apochromatic process lens for color separation with perfect register in the final process also for black and white commercial work

GOERZ GOTAR F6.8, F8, F10
The lens for black and white process and commercial work copying and enlarging

GOERZ HYPAR F2.7, F3

GOERZ APOGOR F2.3
The movie lenses with microscopic definition

GOERZ MOVIE CAMERA ACCESSORIES

Order thru your dealer now for delivery as soon as possible

The C. P. GOERZ AMERICAN OPTICAL COMPANY

Office and Factory

317 EAST 34 ST., NEW YORK 16, N. Y.

AC-9

BACK ISSUES

of The American Cinematographer are available for most months of 1947 and 1948 Many earlier issues also available All contain valuable technical articles and information relative to contemporary motion picture photography The December issues contain an annual index as a guide to content of each year's 12 issues Price of back issues In U S 30c Foreign 40c

THE AMERICAN CINEMATOGRAPHER
1782 N Orange Dr Hollywood 28, Calif

ful show depends upon smooth teamwork between the two or more cameramen and the technical crew During the show, a cameraman must always keep in mind his obligation to his teammate to keep him covered in emergencies In television, the photography must be right the first time There can be no retakes and there are no labs to correct for errors

'T' STOPS

(Continued from Page 306)

5 *Manufacturers' Tolerances* Even in like lenses, permissable tolerances cause variations in focal lengths, in aperture sizes, etc

In the early days of photograhpy, B&H states further, the relatively simple construction of all lenses did not disturb the so called uniformity of the f/stop system However, the science of photography has made rapid strides through the years, and today's lenses are faster, more complex, and composed of more elements, than could have been remotely imagined when the f/stop system was standardized in 1900

In a striking example of the inadequacy of the old system, B&H quotes actual computations showing that a 3-element, coated lens will transmit 94% of the light, whereas a 6 element, uncoated lens will transmit only 50% Thus, *at the same f/stop* these lenses differ from each other in light passage by nearly two to one!

The T system, B&H claims, will change all this because the T stops represent honest measurement of the light actually transmitted by the lens at the various settings In the f/stop system, each f value is mathematically figured from the physical dimensions of the lens, with no thought given to glass, surfaces, or any of the other variable factors In the new T stop system, light is passed through the lens to a photo electric cell where it is actually measured Thus the T value represents the *true* light-admitting ability of the lens, and since the light on every T stop on every lens is actually measured electronically true uniformity is finally achieved T 2 or T 8 on any lens will admit the same amount of light as T 2 or T 8, respectively, on any other lens regardless of differences in focal lengths or maximum apertures

Bell & Howell is careful to answer in advance one of the first questions put forth by amateur photographers who have no reason to determine the mathematics of lens calibration Comparison of the two systems will reveal that for a given, physical diaphragm opening, the T stop rating will be slower than the f/stop Obviously, the same amount of light goes through the particular lens opening at that size, no matter what name is given to the size The f/stop system will indicate a faster rating because the method of figuring it does not allow for any light loss whatsoever The T stop rating will be slightly slower because it does take light loss into account and represents true value The change is simply a change in naming the various diaphragm sizes, and not a change to smaller, slower, apertures Thus a given lens opening might be rated both f/1.9 and T 2, the f value indicating lens speed that does not exist, and the T rating telling the unvarnished truth for the first time

Bell & Howell states that its optical engineers have played leading roles in industry-wide consultations on T stop adoption, and that as a result, a committee of the American Standards Association is now preparing a report adopting the T system as an American Standard

No longer, says Bell & Howell, will newsreel cameramen, for instance, be obliged to calibrate privately their favorite sets of lenses for variations in exposure And when exposure meter manufacturers can base their scales on 100% light transmission, instead of on an arbitrary average, true readings for exposure will be possible

Because the T stop is determined by photo-cell-measured light, and because the light from a given photographic subject is also measured by a photo-cell (within the exposure meter), unerring lens adjustments will be possible With lens calibrations and light from the subject both measured with electronic accuracy, every photo cell meter actually will be matched to every T stop lens

All this naturally poses a problem for many readers of how to reconcile exposure meter readings with the new lens calibrations For the exacting photographer Townsley states that exposure correction may be easily taken into account by using a simple multplying factor to correct the

Only Art Reeves Can Sell The New Model

SENSITESTER

Will Handle Modern Fine Grain Film

NOW AVAILABLE

Line-O-Lite Recording Glow Lamps

ART REEVES MOTION PICTURE EQUIPMENT

1515 N. Cahuenga Blvd. Hollywood 28, Calif.

film speed value to be used For the Weston exposure meter, for example, the factor has been established at 1/0 76, since the value of 0 76 was introduced into the exposure meter equation as a correction factor for lens losses

Bell & Howell's engineers state it even more simply They say that in view of fact most all popular exposure meters are calibrated to account for lens loss, simply advance your Weston speed rating one point Thus, if you are shooting Kodachrome, which has a Weston rating of 8, you would set it up on your exposure meter as 10 when taking readings for use with lenses calibrated in T stops

KALEIDOSCOPIC FILTERS

(Continued from Page 501)

outlined with ink, and when the entire composition is so charted, the various areas are subject to an application of colored gelatins or of transparent color or both, whichever is required to produce the desired effect

The application is illustrated in the accompanying diagrams of an actual scene I recently photographed The larger shows a typical coastal scene in which a nearly white sky and high water reflection prevail and, in addition, the terrain in the foreground is a brownish, almost colorless tone instead of the green desired in the planned pictorial composition

In order to put color into the scene where none exists, the panel of glass is diagrammed as shown in the illustration at the left Subsequently a rectangular polascreen is applied over the entire glass This takes care of the water and other undesirable reflections Then a clear to-blue filter gel is applied over the sky area to lend a natural sky tone instead of the existing washed out white or Santa Monica" sky so familiar to Hollywood cinematographers The sea area, of course, was not modified beyond that imparted by the polascreen The lower third of the picture area was treated with a carefully cut section of green filter gelatine Before this was applied a square was cut out leaving clear that area of the scene in which live action was to take place After the green filter was applied, then green paint was sprayed over the comparatively small area in the scene not corrected by the filter, the paint being carefully matched with the tone of the green filter

Lighting contrast control is also possible by this method of cell-onto-glass by applying N D gelatine of the proper density In one scene of the production cited here, my entire picture composition was shaded except for the center area of the middle background where the main action was to take place My meter indicated a 3 stop difference between the two areas—far beyond the latitude of the film I was work

C. ROSS

FOR

LIGHTING EQUIPMENT

Inkie and Arc Lamps including Required Accessories
Generators—Cables—Boards—Boxes

•

Raby Camera Crane—Dollies—Blimps—Geared Heads

•

GRIP EQUIPMENT

FOR LOCATION AND STUDIO

Parallels—Steps—Platform Ladders
Century Stands—Reflectors—Flags—Scrims

•

SOLE EASTERN MOLE-RICHARDSON CO. DISTRIBUTOR

RENTALS • SALES • SERVICE

•

CHARLES ROSS, Inc.

333 WEST 52nd STREET

NEW YORK 19, N.Y. Circle 6-5470-1



SYNCHRONOUS MOTOR

110 volt A C , single phase 60 cy

for driving

E. K. Cine Special

The motor will run in step with either 16mm or 35mm sound recorders Provided with mounting platform to permit removal of magazine while camera remains mounted

Coupling attaches to single-frame shaft of camera and is mated to spring-steel drive arm of motor gear box. This assures that camera mechanism cannot be damaged if a jam occurs as the spring steel arm will shear This is easily replaced

A knurled knob is on motor armature for rotating while threading On Off switch built into base Platform base threaded for ¼ and ⅜" camera tie-down screws Rubber covered cable with plugs included

Price $150 . . Immediate Delivery

FRANK C. ZUCKER

CAMERA EQUIPMENT CO.

1600 BROADWAY NEW YORK CITY

25 YEARS AGO

With A.S.C. and Members

• JACKSON ROSE, Steve Norton, George Meehan, and L Guy Wilky in the July, 1923 issue of THE AMERICAN CINEMATOGRAPHER discussed the uses and abuses of gauze in cinematography 'Gauze," said Rose, "is properly and more effectively used with the lens at maximum opening '

• JOHN ARNOLD started shooting initial scenes for "In Search of a Thrill," starring Viola Dana, for Metro

• JOHN SEITZ and Victor Milner completed filming Rex Ingraham's production of "Sacramouche' for Metro

• SAM LANDERS was assigned to do the cametawork on Associated First National s production of Thundergate, directed by Joseph de Grasse

• TONY GAUDIO, at the request of Norma Talmadge, was assigned to photograph Rose of All the World "

• FAXON DEAN was shooting the first Paramount Pictures production starring Douglas Fairbanks, Jr, and directed by Joseph Henabery

• ARTHUR EDESON was photographing Douglas Fairbanks, Srs production of The Thief Of Bagdad

• DAVID ABEL was preparing to shoot "Lucretia Lombard,' a Warner Brothers production, having wound up the camera work on "The Gold Diggers for the same studio

• ROLLIE TOTHEROH was doing the camera work on Charlie Chaplin s production, Woman of Paris,' starring Edna Purviance

• NORBERT BRODIN was selected by Frank Lloyd to be his chief cinematographer on his new productions for First National

• CHARLES ROSHER was filming 'Tiger Rose for Warner Brothers and had Ernest Palmer and Reginald Lyons on second unit camera for location scenes

• SOL POLITO was putting the final cinematic touches on Edwin Carewe s production of "The Bad Man for First National

• VICTOR MILNER revealed in a special article in The American Cinematographer that in 1912 he had taught Calvin Coolidge to operate a motion picture camera Coolidge later took the camera north with him and made movies during a moose hunt Coolidge was now President of the United States

• ROBERT NEWARD was awaiting the world premiere of "The Hunchback of Notre Dame which he had photographed for Universal

ing with The situation was corrected by applying a piece of N D filter gelatin over the bright area on the glass panel on the matte box which made possible a balanced over-all exposure for the scene

The method I follow in judging filter densities employs an incident light meter, converted to read reflected light Holding the filter in front of the meter cell, and reading the scene through the filter gives an approximate figure which is correlated with characteristics of the color film used on the production

Where panning or tilting is required, the filters-on-glass procedure undergoes slight change Instead of mounting the glass in front of the matte box, a larger glass panel is used and mounted on supports some distance ahead of the camera, as in making a glass shot The method of outlining the areas to be filtered is the same as for the smaller glass panel, as is that for application of the filter gels The area between the filter glass and the camera, of course, must be blocked out to form a virtual giant matte box This may be done using a black cloth and battens

Still another use for colored filter gelatins is in conjunction with reflectors used on exteriors While shooting location scenes for "Last of the Redmen, I wanted the Indians to appear more like shining copperskins By spraying them with oil and using gold foil reflectors the effect achieved was excellent When there were not enough gold foil reflectors to cover the area, we simply applied large sheets of amber colored filter gelatin over silver reflectors and used them to augment the gold reflectors with good results

Graduated color filters are available on special order from Harrison & Harrison and it was the cooperation of this company which enabled me to switch from experimenting with clear paints on glass to gelatins in making my kaleidoscopic filters. The Mole-Richardson company also have gelatin sheets available in a wide variety of colors To apply the gelatins to glass requires only wetting one surface and smoothing them on To secure them in place for an extended interval of time it is advisable to apply another panel of glass over the gels, forming a sandwich

FILMING STORY OF "MAGIC EYE"

(Continued from Page 312)

animated diagrams) how a reflector works, how large telescopes are used mostly as cameras, and what is seen and photographed through them and the advantages and need of a still larger instrument Incidentally, the 100-inch telescope, painted flat black against a black background, presented some technical problems in color photography The lighting was not only limited by the black subject and a seventy-foot spread for the long shot but also by the objection to any lighting equipment which would appreciably raise the temperature inside the dome, as previously mentioned And the shutters couldn t be opened to admit daylight for the same reason, for the warm air would expand some of the critical parts a few millionths of an inch and thus distort the image of that night s scheduled observation

Still another problem was the confining dome of the observatory which required use of a super wide-angle lens in order to photograph action within the dome I also saw that such a lens would be required in shooting scenes within the optical shop at Palomar and for making several other interior shots I designed and built a triple reducing lens for my Cine Special which photographs a much wider angle than the conventional 25mm lens used on 35mm motion picture cameras in the studios This reducing lens assembly is shown in the accompanying photograph flanked at the sides and the top by a large sunshade The square housing encases three plano-convex lenses—one 2-inch, one 3-inch, and one 6-inch The lenses were obtained from various optical shops Putting the lens together and testing it consumed the better part of two weeks

During the shooting, Hoge and myself were aided materially by the astronomers engineers and opticians, all of whom appreciated what we were trying to accomplish Their cooperation permitted a natural presentation of men actually at work without resorting to actors, reenactments or posed shots against fake backgrounds Then their suggestions and criticisms made the picture absolutely authentic, too After the final narrative script was written, I found it weighted with too many technical terms, so I rewrote the narrative in simple understandable language which was again double checked for accuracy

Production of the 200 inch lens was covered completely Not having been on hand with a camera when glass for the lens was first poured at the Corning Glass works years earlier, nor when subsequent operations in the forming of the giant disk were undertaken, I bridged these events, in order to retain complete continuity, by copying stills showing pouring of the glass These and other stills were photographed by having 8x10 transparencies made of them, then photographing them by means of light projected from the rear Here critical exposure meter readings were necessary

as well as several test runs, in order to insure the photographic result desired

Following this sequence were live action sequences depicting the Cal-Tech campus, the astro-physics building, and the optical and instrument shops there Picturing drawings and scale models of the 200-inch telescope built up an understanding of the instrument and made possible a clearer understanding of the problems involved in its construction In order to convey the extreme accuracy necessary in the grinding and polishing of the giant lens element, I included a brief sequence which shows how small, two-inch lenses were originally ground by hand, and how larger lenses and mirrors require increasingly larger and more complex machines and tools

The Foucault test climaxes the polishing of the 200 inch mirror When, after eleven and one-half years, the final accuracy of the concave surface is measured by the reflection of a tiny beam of light, actual shots were made of this process in which a pattern of light and shadow indicates variations in the surface of only two-millionths of an inch Imagine using a flashlight bulb to photography an area seventeen feet wide, and in color!

The loading and moving of the mirror in its cell, 35 tons of steel and glass, was one of the most amazing feats of heavy but delicate transportation ever recorded A 58-wheeled trailer pulled and pushed by three powerful tractors was escorted by the California Highway Patrol over cleared and in some cases specially built roads and reinforced bridges to Palomar Mountain This sequence added considerable suspense and scenic interest to the picture, and involved some "jack rabbit" operations on my part in order to catch the dramatic transportation highlights with my camera The route travelled by the trucks was cleared well in advance of the truck and heavily guarded Thus, despite my connection with filming the project for Cal-Tech, I frequently encountered difficulty in getting my car on the highway again after making a shot in order to speed ahead for the next camera setup But by poring over maps and planning many shortcuts in advance, I managed to make the appointed camera positions in ample time to get set up and ready for the trucks when they arrived on the scene

Looking through a large telescope reveals millions of stars that can't be seen with the naked eye These visible stars can be photographed in about five minutes with a still camera Obviously, a longer time exposure reveals more stars, billions more in fact, stars which can never be seen except on negatives exposed continuously, hours at a time, sometimes for several successive nights As the earth rotates, the telescope must be moved con-

(Continued on Next Page)

SALES • SERVICE • RENTALS

35 mm. • 16 mm.

CAMERAS·MOVIOLAS·DOLLYS

Complete Line of Equipment for Production Available for Rental

Mitchell: Standard - Hi-Speed - NC - BNC - 16 mm.
Bell & Howell: Standard - Shiftover - Eyemos
Maurer: 16 mm. Cameras
Moviola: Editing Machines - Synchronizers

SPECIALISTS IN ALL TYPES OF CAMERA REPAIR WORK. LENSES MOUNTED

FRANK C. ZUCKER
CAMERA EQUIPMENT CO.
1600 BROADWAY NEW YORK CITY

"Debloopers"

Rentals
Sales and Repairs
Mitchell
Bell & Howell
Eyemo
Akeley
Wall
Cameras

Designing
Manufacturing
Lens Mountings
16 and 35 mm. Ballar Lenses
Photometric "f" Scaling

John Clemens - Erwin Harwood
National Cine Equipment
20 West 22nd St., New York 10

Cine Special Repairs, Modifications

Animation Stands • Motors • Magic Eye Cameras

EVERYTHING PHOTOGRAPHIC
AND CINEMATIC
FOR PROFESSIONAL AND AMATEUR

The World's Largest Variety of Cameras and Projectors Studio and Laboratory Equipment with Latest Improvements as Used in the Hollywood Studios New and Used BARGAINS

HOLLYWOOD CAMERA EXCHANGE
1600 CAHUENGA BOULEVARD
HO 3651 • Hollywood, Calif. • Cable Hocamex

clip, sign and mail...

with your check or money order for $2.50 and we'll send you THE AMERICAN CINEMATOGRAPHER for 12 months starting with the next issue

Name

Address

City *Zone* *State*

☐ Check ☐ Money Order is enclosed

MAIL TO: American Cinematographer, 1782 N. Orange Dr., Hollywood 28, Calif.

Current Assignments of A. S. C. Members

Members of The American Society of Cinematographers were engaged as Directors of Photography in the Hollywood Studios during the month of August, as follows:

Columbia

• BURNETT GUFFEY Knock On Any Door (Santana Prod.) with Humphrey Bogart and Susan Perry Nicholas Ray, director

• LESTER WHITE Jungle Jim with Johnny Weismuller and Virginia Grey William Berke, director

• JOSEPH WALKER "Mr. Soft Touch" with Glenn Ford and Evelyn Keyes Gordon Douglas, director

• PHIL TANNURA The Lone Wolf and His Lady with Ron Randell June Vincent and Alan Mowbray John Hoffman director

• VINCENT FARRAR The Crime Doctor's Diary with Warner Baxter Lois Maxwell and Adele Jergens Sevmour Friedman director

Eagle-Lion

• WILLIAM H. GRELNE The Big Car," (Technicolor) with Lon McCallister and Peggy Ann Garner Phil Karlson director

• JOHN ALTON Red Stallion of the Rockies (Cinecolor) with Jean Heather and Arthur Franz Ralph Murphy director

Independent

• WINTON HOCH Tulsa, (Walter Wanger Prod.) (Technicolor) with Susan Hayward and Robert Preston Stuart Heisler, director

• ERNEST LASZLO The Lucky Stiff, (American Enterprises UA) with Dorothy Lamour, Brian Donlevy and Claire Trevor Lew Foster, director

• LEE GARMES The Best Things In Life Are Free, (Enterprise) with Barbara Bel Geddes, Robert Ryan, James Mason John Berry, director

• WILLIAM C. MELLOR Blonde Heaven, (Lester Cowan-UA) with the Marx Brothers and Ilona Massey David Miller, director

• GILBERT WARRENTON Parole," (Orbit-E. L.) with Michael O'Shea Turhan Bey, and Evelyn Ankers Alfred Zeisler director

• WALTER STRENGE A Dare With Murder' (Falcon Prod.) with John Calvert and Catherine Craig Jack Bernard director

• FRED H. JACKMAN JR. Canadian Pacific (Nat Holt-20th) (Cinecolor) with Randolph Scott and Jane Wyatt. Edwin L. Marin director

• LUCIEN ANDRIOT Outpost In Morocco (Moroccan Pictures UA) (Goldwyn) with George Raft and Marie Windsor Robert Florey director

• BENJAMIN H. KLINE, "Last of the Wild Horses, (Lipperr Screen Guild) with James Ellison Jane Frazee and Mary Beth Hughes Robert L. Lipper, director

• WILLIAM A. SICKNER, Rose of Cimarron, (Alson Prod 20th) with George Moorgomery, Rod Cameron and Ruth Roman Lesley Selander, director

• JOHN ALTON, Reign of Terror,' (Walter Wanger-EL) with Robert Cummings and Arlene Dahl Anthony Mann, director

M-G-M

• CHARLES SCHOENBAUM Little Women (Technicolor) with June Allyson, Margarer O'Brien, Eliz Taylor Janet Leigh and Perer Lawford Mervyn LeRoy, director

• HARRY STRADLING Barkleys of Broadway,' (Technicolor) with Fred Astair and Ginger Rogers Charles Walters, director

• GEORGE J. FOLSEY, JR., Take Me Our To the Ball Game, (Technicolor) with Frank Sinatra Esther Williams and Gene Kelly Busby Berkeley, director

• ROBERT H. PLANCK Little Women' (Technicolor) with June Allyson Margarer O'Brien Eliz Taylor, Janet Leigh and Peter Lawford Mervyn LeRoy director

Monogram

• HARRY C. NEUMANN. Call of the Cactus' with Jimmy Wakely and Cannonball Taylor Lambert Hillyer, director

• MARCEL LEPICARD Incident with Warren Douglas and Jane Frazee Hall Shelron director

• MACK STENGLER Joe Palooka in the Big Fight with Joe Kirkwood Jr. and Lina Romay Cy Endfield, director

• HARRY C. NEUMANN. "Gunning for Justice. with Johnny Mack Brown and Evelyn Finley Ray Taylor director

Paramount

• LEO TOVER The Heiress with Olivia DeHaviland and Sir Ralph Richardson William Wyler director

• RAY RENNAHAN "Streets Of Laredo,' (Technicolor) with William Holden, William Bendix and Mona Freeman Leslie Fenton, director

• JOHN F. SEITZ "One Woman," with Alan Ladd, Donna Reed and June Havoc Lewis Allen director

R-K-O

• HARRY WILD Interference, with Victor Mature and Lucille Ball Jacques Tourneur, director

• J. ROY HUNT Gun Runners with Tim Holt, Richard Martin and Martha Hyer Frank McDonald director

• ROBERT DEGRASSE Follow Me Quietly" with William Lundigan and Dorothy Patrick Richard Fleischer director

20thCentury-Fox

• ARTHUR MILLER Three Wives with Jeanne Crain, Linda Darnell and Jeffrey Lynn Joseph L. Mankiewicz director

• HARRY A. JACKSON Chicken Every Sunday,' with Dan Dailey, Alan Young and Celeste Holm George Seaton, director

• CHARLES G. CLARKE, "Sand, (Technicolor) with Mark Stevens Coleen Gray and Rory Calhoun Lou King, director

• JOSEPH LASHELLE The Fan," with Jeanne Crain and George Sanders Otto Preminger, director

• ARTHUR ARLING "Mother Is a Freshman" (Technicolor) with Loretta Young and Van Johnson Lloyd Bacon, director

• JOE MACDONALD "Down to the Sea in Ships,' with Richard Widmark, Cecil Kellway and Dean Stockwell Henry Hathaway, director

Warner Brothers

• ROBERT BURKS The Fountainhead with Gary Cooper and Patricia Neal King Vidor, director

• WILLIAM E. SNYDER The House Across the Street with Wayne Morris and Janis Paige Richard Bare, director

• CARL GUTHRIE "Somewhere in the City with Viveca Lindfors and Edmond O'Brien Vincent Sherman, director

• ERNEST HALLER, 'Happy Times" (Technicolor) with Danny Kaye and Barbara Bares Henry Koster, director

• WILFRID CLINE Two Guys and a Gal,' (Technicolor) with Dennis Morgan Jack Carson and Doris Day David Butler, director

• KARL FREUND Montana, (Technicolor) with Errol Flynn and Alexis Smith Ray Enright director

'GIANT EYE'

(Continued from Page 321)

tinuously during the exposure with unbelievable accuracy, to hold the image of the stars

Limitations on film speed and static views make motion pictures through a telescope meaningless generally, but again still transparencies were copied for this picture to show the beauties the mysteries, and the measurable data of our vast universe To trained observers, the 200-inch telescope will present the greatest and most unknown frontier that the mind of man has ever explored We must remember that steam and electricity and atoms were once impractical laboratory curiosities No man can foresee what modern astro-physics may bring forth in this scientific age The stars have already revealed new elements, sources of atomic energy, and confirmation of the sweeping theories of Copernicus and Einstein And there is that age old satisfaction men have always had in looking with wonder at the heavens feeling our destiny is somehow locked in their dim and distant secrets

LIGHTING SMALL SETS

(Continued from Page 309)

on location most of the time he will want lighting units that fold up for easy portability, but which are sturdy enough to be hauled about and simple enough to be set up quickly in a new location

The matter of budget is bound to rear its ugly head unless the cameraman is fortunate enough to have unlimited funds to spend on equipment Top-grade lighting units are fairly expensive and would represent quite an investment for the cameraman or producer who shoots few interior sequences In such cases, it is better to rent lighting units than to tie up a large sum of money in purchased equipment But if the cameraman knows that he will be shooting interior sequences frequently it is wiser by far to invest in substantial lighting units If his funds are limited, he will do well to invest in a

few good basic units (which may be bought used) and fill in with photofloods or improvised reflector set-ups

Let's take a look at the types of small set lighting units available and compare the characteristics of each, starting with the simplest units and working up to the more elaborate pieces

Photofloods—These are high-intensity incandescent bulbs available in three sizes (250 watts, 500 watts, and 1,000 watts) The two smaller bulbs, numbers 1 and 2, have standard bases and will fit any household screw socket The larger bulb, number 4, has a larger mogul type base and must be used in a special socket The average burning life of these bulbs is about six hours, and they are most effective when used in metal reflectors Photofloods are very useful when mounted in banks for high-intensity general illumination In professional cinematography they are often used to boost the general light level, especially in color photography where highet levels of illumination are required

Reflector Spots and Floods—These are "mushroom" shaped units with reflectors built into the bulbs Their chief advantage is that they are complete in themselves and need no additional reflectors The floods can be used very successfully in banks for general illumination The spots give out a concentrated, softly diffused beam rhat serves as a good modeling light in black and white cinematography

The Dinky-Inkie—This is the smallest standard spotlight unit used in motion picture photography, and it is a real boon to any cameraman Carrying a bulb of 100 to 150 watts, it is extremely versatile and portable Irs small size enables it to be easily concealed behind furniture ot props on the set It has a beam that can be focused ftom 4 to 44 degrees, and a complete line of accessories is available for use in conttolling the light

The Baby Keg light—A widely used 500-750 watt sporlighr that is valuable as a light-weight all-purpose unit It is a basic unit in black and white filming and valuable as a secondary unit in color cinematography. The Foco spot attachment that fits onto this unit permits a wide variety of unusual effects.

The Junior Spotlight—A 1,000-2,000 watt unit is an excellent basic light for the cinematographet Equipped with a 2,000 watt bulb, it also serves well as a key-light for black and white cinematography and can be similarly used in color photography when a wider apertute is used The Junior Spot combines adequate illumination with easy portability, and is equipped with a sturdy stand that folds up into a small space A complete line of accessories affords the ultimate in light control

The Senior Spotlight—A 5,000 watt unit that is invaluable to the professional cinematographer It is sufficiently bright to simulate outdoor sunlight on an interior set, as well as to cover large areas with general illumination As a key-light in color filming ir is unexcelled, since it allows the cameraman to stop down his lens aperture for greatet depth of-field It is a light bright enough to dominate the key of a set-up without getting lost in the superimposed light of other units rhat may be used for genetal illumination For this reason, it is especially useful in creating a modeled effect in color filming The Senior Spot is, however, an expensive unit, both from rhe srandpoint of cost and the amount of current used The newly-tutned professional cameraman will do well to make sure of his needs before investing in this unit

Single and Double Broads—These units accomodate 500 or 750 watt globes in a lamphouse featuring a highly diffused lens The singles have one bulb, while the doubles carry two The quality of light is extremely soft ideal for filling the shadow side of a face in close-up The Broads ate also useful in casting an even tone of light on backgrounds, as well as for softening hatsh shadows cast by the key-light Broads are especially adapted to black and white cinematotgaphy because they are relatively weak in intensity, but the double broad is often used in color close-ups as a fill light for producing translucent shadows

The Cinelite—A recently developed general-purpose unit consisting of a metal stand ropped with a parabolic reflector into which is fitted a No 4 photoflood globe This unit was especially designed as a portable general-illumination source fot color photography, and it fills the bill perfectly On latge sets, several of these units can be mounted on an overhead pipe to flood the stage area

The above standatd lighting units are generally available from any studio lighting dealer Fot the spotlights desctibed accessories ate available such as barn doors, snoots, diffusers and daylight filters (for use when mixing daylighr with artificial light in color filming)

In addition to the lighting units themselves suitable electtical wiring facilities must be obtained For location shooting, the main piece of equipment will be a master switch box with a heavy cable that can be tapped into city lines or existing current on the scene Plugging into this box will be two ot three other cables each terminating in a switch box capable of accommodating up to six lighting units For semi permanent set-ups, such as a building converted to a shooting stage a main 'hot-line can be brought in and installed in a metal conduit Standard srage boxes can be attached to this line, and the units fitted with srage plugs

The amount of cutrent needed will depend upon the number of units to be used and the amperage they will draw.

Insist on
PEERLESS Film Treatment
For Proven Permanent Protection

1 Keeps Film Pliable despite climatic and storage conditions
2 Toughens Film . . against scratches, digs, and long, hard wear
3 Helps Film Resist fingerprints, handling marks, dirt, oil water.
4 Lubricates Film . . to ease projection, especially during first runs.

New Low Prices!
Write for price list.

New Folder! "20 Questions" containing information on film treatment and the list of laboratories equipped to do Peerless Processing Write for your free copy

PEERLESS FILM PROCESSING CORPORATION
165 West 46th Street, New York 19, N. Y

To PRODUCERS...
A British specialist 16mm film unit can undertake your coverage on people, places and events in BRITAIN and EUROPE.
•
16mm ORIGINALS Supplied
•
Peak Films Productions
171 Victoria St, London S. W. 1, Eng

BLACK AND WHITE • KODACHROME
ENLARGED 8 to 16 REDUCED
DUPLICATES 16 to 8
GEO. W. COLBURN LABORATORY, Inc.
164 N. Wacker Dr., Dept. A, Chicago 6, Ill.

MOVIOLA
FILM EDITING EQUIPMENT
Used in Every Major Studio
Illustrated Literature on Request
Manufactured by
MOVIOLA MANUFACTURING CO.
1451 Gordon Street Hollywood 28 Calif

GIL MORGAN Says
Read MY magazine, too! It's chuck full of photographic news and info on new equipment we can deliver now! Write for your FREE copy of the MORGAN CAMERA NEWS today.
MORGAN CAMERA SHOP
6262 Sunset Blvd • Hollywood 28, Calif.

Roughly speaking one ampere of current will be required for each 100 watts of illumination The standard house circuit is wired to accept only 10 to 15 amps Overloading such circuits, even when heavier fuses are installed, may result in burned out wiring and an actual fire hazard So if you are planning to use a number of heavy lighting units, be sure that your electrical facilities are strong enough to accomodate the current required

How many units to buy depends as we have said befote, upon the types of filming done The minimum basic requirements for professional lighting quality, however, should include one Junior Spotlight, 3 Baby Keg-lites, 2 Dinky-Inkies and one single or double Broad, or their equivalent If filming is ro be done in color, at least six Cinelites should be purchased in addition to the other units A Senior Spotlight is a very valuable unit to have on any sort of large scale production Banks of reflectors made with sockets mounted in a row on a wooden base are good general illumination sources for use on location

It is wise for the producer or cameraman just going into professional production to analyze his own needs purchase the minimum numbet of lighting units, and gradually add any additional units which time and experience indicate a need If his funds are limited, he may purchase a very few professional lighting units and supplement them with home-made reflector and strip light units using photoflood lamps as a light source

NFXT MONTH Part II—Basic Set Lighting

BULLETIN BOARD

(Continued from Page 296)

Seely, Montana, fifty miles northwest of Missoula The property, to be developed as one of America's finest dude ranches, has four lakes and five streams heavily stocked with trout, two ski runs and a private landing field equipped to handle standard airliners as well as private planes Recently Ralph Staub, ASC, journeyed there with Glenn Ford, Eleanor Powell, Sonny Tufts and Charlie Ruggles to produce one of his 'Screen Snapshots' short subjects Life magazine's photographers will cover a grizzley bear hunt there in October

•

CORRECTION In Fred Gately's article describing the Spectra meter last month, the 6th line in second paragraph on page 280 should have read, degrees *or 3200 degrees* Kelvin, and either the light itself In the 23rd line, 1st paragraph, 2nd column, same page, the word *separation* should have been *situation* Our proofreader's apologies to Fred Gately and our readers

WHAT'S NEW

in equipment, accessories, service

FIFTY-SEVEN brand new '16mm Professional' Mitchell cameras, part of large Navy contract order.

Mitchell Anniversary

This month, Mitchell Camera Company Glendale, Calif., celebrates the first anniversary of the introduction of its 16mm Professional motion picture camera by delivering the first group of cameras—57 in all—on its contract with the U S Navy Cameras, pictured above, will be distributed among the Navy's various motion picture units

Designed to meet the need for really professional equipment in the Navy's expanding training film production activities, these cameras will soon be manned by carefully trained Naval cinematographers in a program of research and training film production

The Mitchell '16mm Professional,' which is virtually identical to the famed Mitchell 35mm studio camera, incorporates the same proven features of its studio counterpart Every type of photographic effect possible with a 35mm camera is also possible with the Mitchell 16mm Professional '

50th Anniversary

September 13th marks the 50th anniversary of the day in 1898 when Fred Schmid, a young instrument-maker applied for a position with the Goerz Optical Works in Berlin-Friedenau, Germany After an interview with C P Goerz, founder of the Goerz enterprises latter offered to send him to America to open a branch factory there

The American firm was incorporated in 1906 as the C P Goerz American Optical Company The German Goerz Company was merged in 1926 with the Zeiss Ikon Corporation in Germany Today the American Goerz firm is the only company which supplies a full line of the celebrated Goerz photo-lenses Fred Schmid, at first in charge of production, was made general manager in 1910, vice president of the American company in 1920, and finally president in 1937

16mm. Tape Recorder

Combining a typical motion picture engineered high fidelity synchronous 16mm recorder with a 16mm high fidelity magnetic tape recorder, the Cine-Pro Corp 106 West End Ave, New York City, offers a versatile magnetic recording device that affords the 16mm film producer the means for recording sound for his films at a considerable saving over photoelectric recording

The tape, which has standard 16mm film perforations, travels at a speed of 14.4 inches per second or twice ordinary 16mm film recording speed, which in-

CINE-PRO magnetic tape recorder uses perforated 16mm film is synchronous motor driven.

sures a frequency response beyond 13,000 cycles A combination forward-reverse switch affords quick rewinding of the recorded tape A footage counter indicates the return of tape to exact starting point Large reel arms permit use of tape in 1600 foot spools to provide a maximum of 22 minutes of continuous recording As with all magnetic recording mediums, the tape may be erased and re-used hundreds of times

The synchronous motor drive of recorder affords use of recorder for lip-sync sound recording with any camera driven by a synchronous motor Fidelity of track produced by the Cine Pro magnetic tape recorder is said to exceed that of the finest 35mm photoelectric recorded sound track due to extremely low background noise inherent in magnetic recording

S.O.S. In New Quarters

SOS Cinema Supply Corp., New York, celebrated its 22nd anniversary recently by moving into its wholly-owned and completely new quarters at 602 West

52nd St Founded 22 years ago by J A Tanney, company president, organization now commands 3½ acres of floor space and a substantial and highly expert staff of camera and laboratory technicians

When sound was first added to silent pictures, the new art required the services of skilled sound technicians, and very few trained men were available

Tanney formed Service on Sound Corp (hence SOS) with a nucleus of ex-radio and broadcasting engineers, to give periodic and emergency service to the industry

As the big Electrics expanded their own service departments and rental arrangements, SOS swung into sales, repairs and maintenance, changing its corporate title to Sales on Sound In a few years, with the emphasis definitely on sales, it adopted its present name SOS Cinema Supply Corp

Claiming to offer complete coverage of the entire line of equipment needed by cinematographers the company today handles every known make of cinematic, printing, processing, lighting and recording apparatus, either as new or as reconditioned equipment, or both SOS does its own reconditioning with the help of

SOS Cinema Supply Corpn, of New York recently moved to these new quarters

the most advanced machine tools and extremely skilled and versatile machinists

While many patrons visit its New York headquarters, SOS conducts its business largely via mail order Because of this policy, Tanney explains, the company rarely sends out sales representatives, except on major undertakings

New Cine-Special

The famous Cine-Kodak Special camera now features a new type of lens turret, and improved reflex, eye-level, and peep-sight viewfinders It also will be equipped with the new Kodak Cine Ektar 25mm f/1.4 lens as standard.

The newly designed lens turret—most apparent outward change in the camera—is equipped with integral adapters which accept the full line of Cine-Kodak interchangeable lenses The adapters are of ball-bearing construction and lenses, once seated, are locked securely in position Lens block is angled to prevent second lens from interfering with the first—either physically or optically—when the first is in picture-taking position Any two current Cine-Kodak accessory lenses—regardless of speed or focal length—can

CINE-KODAK Special' with re-designed 2-lens rotary turret new Cine Ektar lenses

be used in combination and with easy interchangeability

Changes have also been made in the eye-level finder system. A separate front-finder element is now made for each of the full line of Cine-Kodak lenses Finders snap onto the turret

Improvements in the peepsight are such that the sight can now be adjusted to correct for parallax at film-to-subject distances ranging from 2 feet to infinity

Owners of Cine-Kodak Special cameras who wish to have their cameras converted to the new model may do so through the Kodak Repair Department, it was announced

The Cine-Kodak Special II camera is priced at $860, plus tax

KEEPING UP WITH PHOTOGRAPHY

(Continued from Page 298)

minutes to remove the silver halide formed from the colloidal silver of the filter layer and from the fine-grained silver that was produced as fog in the first developer without removal of the silver halide of the sound-track of picture records This treatment produces clean highlights for the sound track record The sound-track is then redeveloped for about 15 to 30 seconds by edge application of a strong black-and-white developer A final fixing for about 2 minutes completes the treatment of the film



THREE PROFESSIONAL HIGH FIDELITY MACHINES PRICED TO DEFY ALL COMPETITION

Cine-Pro SIXTEEN MM

FILM RECORDER

FILM PHONOGRAPH

TAPE RECORDER

Cine-Pro CORPORATION

106 WEST END AVENUE

NEW YORK 23, N.Y. TRAFALGAR 3-1411

RUBY CAMERA EXCHANGE

Rents . . Sells . . Exchanges

Everything You Need for the

PRODUCTION & PROJECTION

of Motion Pictures Provided by a Veteran Organization of Specialists

35 mm. . . . . 16 mm.

IN BUSINESS SINCE 1910

729 Seventh Ave., New York City

Cable Address RUBYCAM

Scheibe's FILTERS In World-Wide Use

GRADUATED FILTERS - for Moonlight and Night Effects in Daytime Diffused Focus and Fog producing Filters. The Original Monotone and many others.

WRITE FOR FOLDER TWinoaks 3100

SINCE 1916

George H. Scheibe

ORIGINATOR OF EFFECT FILTERS

1927 WEST 76TH ST LOS ANGELES, CAL.

Classified Advertising

RATES: Ten cents per word—minimum ad $1 00 Ads set in all capital letters, 60c per agate line (12 agate lines per inch)
No discounts on classified advertising Send copy to editorial office, 1782 N Orange Dr, Hollywood 28 California

FOR SALE

BASS OFFERS BARGAINS

SPECIAL—Brand new Professional Jr friction head pan and tilt tripod complete with case Save $40 00 Regular $190 00 price including all taxes Our price ___ $150 00
35mm Eyemo 3-speed Cooke F 2 5 lens case ___ $235 00
B & H Eyemo Air Corps A 4 A Model 3-speed 1" wide angle F 4 5 fixed focus 2 Eymax F 2 8 focusing 6 Eymax F 4 5 focusing 10" F 4 5 Eymax focusing filters variable optical view finder, carrying case ___ $595 00
New 16mm Auricon Single System Sound complete outfit including power pack battery amplifier, tripod etc ___ $1725 00
400-ft inside magazine DeBrie with 2" Tessar F 3 5 lens case and four magazines $165 00
WRITE YOUR WANTS BASS MAY HAVE IT FOR LESS CINE HEADQUARTERS FOR 38 YEARS BUY SELL AND TRADE
BASS CAMERA CO 179 W MADISON ST CHICAGO 2 ILL

35mm SPECIALS

35MM INTERMITTENTS — precision machining excellent design Perfect for Printers Animation Cameras, Slide Film Cameras and for silencing and modernizing most on picture cameras Double pull-down claws and double registration pins at aperture Entire unit in light-tight metal case to accommodate 200 foot roll complete with take-up Light trap at aperture These units are NEW Will sell for $150 00 each Write for quotations on quantity purchase
AFP
1600 BROADWAY — SUITE 1004
NEW YORK 19 N Y

MORGAN CAMERA SHOP

The Complete Camera Store

We buy, sell, trade, rent

Free copy of MORGAN CAMERA NEWS sent on request

6262 Sunset Boulevard • • Hollywood 28 Calif

Two BI-PACK BELL & HOWELL 400 magazines—brand new condition—$250 00 each
Complete 16 & 35mm laboratory and sound recording services for the Midwest producer
ESCAR MOTION PICTURE SERVICE INC 7315 Carnegie Ave Cleveland 3 Ohio Phone Endicott 2707

ONE SET OF BAUSCH & LOMB BALTAR coated lenses in Mitchell Mounts 35mm 50mm and 75mm ___ $775 00
One New Eastman Cine-Special 16mm Camera with coated lens ___ $575 00
Box 1051, AMERICAN CINEMATOGRAPHER

WE BUY SELL AND RENT PROFESSIONAL AND 16mm EQUIPMENT NEW AND USED WE ARE DISTRIBUTORS FOR ALL LEADING MANUFACTURERS RUBY CAMERA EXCHANGE 729 Seventh Ave New York City Established since 1910

WE Buy Sell Trade Cameras Projectors Laboratory and Cutting Room Equipment 8-16-35-mm We pay highest prices Carry one of the most diversified stocks in America Mogull's Camera & Film Exchange 68 West 48th Street New York 19 N Y

BRAND NEW 35mm Navy type O sound projectors Model XO Complete with speakers and amplifiers Specially priced Camera Mart Inc 1614 No Cahuenga Hollywood HE 7373

LAMPS—5000 W 2000 W 3200 deg K MP-CP Screw base and Mogul 50% off The Warren Corporation 901 Ridge Ave Pittsburgh 12 Pa

COMPLETE 16mm SOUND FEATURES Islightly used for outright sale Write New England Film Exchange 833 Main St Southbridge Mass

CINE SPECIAL Filmo 70DA for sale Ryemons 2901 Main Houston 2 Texas

FOR SALE

35MM CINE LENS—Available on 15 day trial Satisfaction guaranteed Some wonderful values from our tremendous lens stocks

For Eyema Camera - Lenskoted - Focusing Mounts	
1 F4 5 Bell & Howell Wide Angle (Fixed Focus)	$ 74 50
1 F2 3 Kinar Wide Angle	99 50
2 F1 5 Gallmeyer	199 50
2 F2 Schneider Xenon	119 50
3 F2 3 Bausch & Lomb Baltar	179 50
5' F2 3 Astro Pan Tachar	343 75
6 F4 5 Taylor Hobson Cooke	125 00
10 F4 5 Bell & Howell Eymax	205 00
14" F5 5 Schneider Tele-Xanar	165 00
400 35MM Magazines for Eyemo	69 00

Exceptional Stock of Rebuilt Eyema Cameras
Write for details

For DeVry Cameras - Lenskoted - Focusing Mounts	
1 F4 5 Bell & Howell Wide Angle	$ 74 50
2 FI 9 Ultra Stigmat	69 50
For Mitchell Cameras Lenskoted	
2" FI 5 Hugo Meyer Primoplan Focusing Mount	$199 50
3 ' FI 9 Hugo Meyer Primoplan Focuring Mount	199 50
18 F5 6 Telephoto Focusing Mount	162 50

Stocks constantly changing Write for complete listings and trae catalog Address inquiries to Mr T Jones Burke & James Inc 321 So Wabash Chicago Illinois U S A

FOR SALE BELL & HOWELL Standard Camera 35mm 50mm 75mm 100mm F 2 3 lenses High Speed Movement, Single system sound Modulite Galvanometer variable density amplifier excellent sound quality complete $4500 00 BERETANIA THEATRE Honolulu T H

CLASSIFIED ADS

in

THE AMERICAN CINEMATOGRAPHER

GET RESULTS

says

ROBERT GROSS

of

AFP DISTRIBUTORS
NEW YORK CITY

who wrote us on June 4th as follows

"You may be interested in knowing that we have disposed of all the film viewers we had available for sale solely as a result of the classified ad placed in your publication."

Put this Classified Advertising Section to work for you!

If you have equipment and accessories to sell—35mm or 16mm new or used—if you have services to offer something to trade—A classified ad in THE AMERICAN CINEMATOGRAPHER will bring you

IMMEDIATE RESULTS!

FOR SALE

FOR SALE BELL & HOWELL Standard Camera 35mm 50mm 75mm 100mm F-2 3 lenses High Speed Movement Single system sound Modulite Galvanometer variable density amplifier excellent sound quality complete $4500 00 BERETANIA THEATRE Honolulu T H

CAMERA & SOUND MEN

SERVICE TO PRODUCERS

Camera and sound men artistically and scientifically skilled well equipped **MODERN 1200 Square feet SOUND STUDIO** ideally suited for Television work High-fidelity play-back Stage set construction

ROLAB

Sandy Hook Connect cut

90 minutes from New York City

Telephone Newtown 581

Ask for rates

KODACHROME stock shots of the Nation's Capitol Also available for Eastern 16mm assignments George C Pace 605 29th Street South Arlington Virginia PHONE JACKSON 1926 J

WANTED

WANTED TO BUY FOR CASH
CAMERAS AND ACCESSORIES
MITCHELL B & H EYEMO DEBRIE AKELEY
ALSO LABORATORY AND CUTTING ROOM EQUIPMENT
CAMERA EQUIPMENT COMPANY
1600 BROADWAY NEW YORK CITY 19
CABLE CINEQUIP

EYEMO 71Q Spider turrets particularly now but almost anything worth reselling SOS Cinema Supply Corporation 602 W 52nd Street New York 19

WANTED 12 volt wild motor for B & H Standard camera Orville Snider P O Box 32 North Hollywood Calif

PREWAR EYEMO DeVRY or similar 35mm portable automatic Box 1462 Pinewood Station Miami Florida

WE PAY CASH FOR EVERYTHING PHOTOGRAPHIC Write us today Hollywood Camera Exchange 1600 Cahuenga Blvd Hollywood

STUDIO & PRODN. EQUIP.

2000W FRESNEL Studio Spots $57 50 MR type 2000W on rolling stand $99 50 Used Auricon Recording outfit $495 00 Neumade 35mm Filmsacks 76 high $39 50 Bellhowell Automatic 16/35 hot splicer $795 00 B & H Single System Recording & Studio Camera with rack-over magazines 6 fast Astro lenses 4 position amplifier 4 mikes power supply etc reduced—$5 250 00 Western Electric Preview Magazines $395 00 Bodde Process Screens $2 40 sq ft W E 35mm Sound Moviola $795 00 Mitchell Plywood Blimp $1 49 50 Klieglite 2000W Rifle, $79 50 Neumade Automatic Film Cleaners $159 50 Send for latest Catalog New Address S O S Cinema Supply Corporation 602 W 52nd Street New York 19 N Y

STUDIO FOR SALE

FAMOUS FILMCRAFT EDISON STUDIO FOR TELEVISION PRODUCTION COMPLETELY EQUIPPED SOUND STAGES MITCHELL CAMERA EQUIPMENT PROCESS PROJECTION HEAVY GENERATORS RCA SOUND CHANNELS LIGHTS FILMVAULTS EXECUTIVE OFFICES DRESSING ROOMS SHOPS PROPS LONGTERM LEASE REASONABLE RENTAL OR SALE WIRE OR PHONE FOR DETAILS S O S CINEMA SUPPLY CORPORATION 602 W 52nd STREET, NEW YORK 19

She owes her "ripe old age" to him . . .

HOWEVER skillfully she might play her part, this young actress would still seem more girl than grandmother—save for the creative ingenuity of the make-up man.

By deft application of grease paint and putty, he has added years to her appearance . . . and conviction to her role.

This is but one instance of the magic at the make-up man's command. He does as much and more for film folk who must be transformed to Jekyll, Cyrano, gnome, or Manchu.

When these characterizations reach audiences successfully, it is because the make-up man combines cosmetic artistry with full knowledge of his medium. And, in knowing films, he is aware of what is done to help his work by the versatile members of the Eastman motion picture family, famous films for more than fifty years.

EASTMAN KODAK COMPANY
ROCHESTER 4, N. Y.

J. E. BRULATOUR, INC., DISTRIBUTORS
FORT LEE • CHICAGO • HOLLYWOOD

BELL & HOWELL

Filmosound

The 16mm Sound Film Projector That Delights The Discriminating

The more demanding you are of quality in sound film reproduction . . the more critically you scrutinize screened pictures and listen to reproduced sound . . . the more certain you are to appreciate fully the superiority of a Bell & Howell Filmosound

For every Filmosound is built up to a standard, not down to a low price. And that standard is so high that Filmosounds consistently delight the most discriminating.

Ask your dealer about Filmosounds Examine one critically Check its performance. Then you'll see why this is *the* projector to meet your most exacting requirements.

Bell & Howell Company, 7148 McCormick Road, Chicago 45. Branches in New York, Hollywood, Washington, D. C., and London

Precision-Made by

Bell & Howell

Since 1907 the Largest Manufacturer of Professional Motion Picture Equipment for Hollywood and the World